# Eaton LP-CC-25

## Catalog Number: LP-CC-25

Eaton Bussmann series LP-CC fuse, Current-limiting time-delay fuse, Rejection style, 25 A, Dual, CC, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 20 kAIC at 300 Vdc|200 kAIC at 600 V, Melamine tube, 10

#### General specifications



Catalog Number

Eaton Bussmann series LP-CC fuse

LP-CC-25

UPC

EAN

051712180283

5027590446983

Product Length/Depth

Product Height

0.41 in

1.5 in

**Product Width** 

**Product Weight** 

0.41 in

0.15 lb

Warranty

Compliances

Not Applicable

CE Marked

RoHS Compliant





### **Product specifications**

Fuse indicator

Non-indicating

Special features

Rejection style

Interrupt rating

200 kAIC at 600 Vac 20 kAIC at 300 Vdc

Number of elements

Dual

Connection

Ferrule end x ferrule end

Response time

12 sec at 200%

Quantity

10

Material

Melamine tube

Amperage Rating

25 A

Type

Current-limiting time-delay fuse

Class

Class CC

Voltage rating

600 Vac, 300 Vdc

Application

Specialized circuits and industrial control

Packaging type

Standard

#### Resources

#### Catalogs

LP-CC-25~LOW PEAK CC TIME DELAY

Bussmann series complete full line catalog no. 1007

Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - LP-CC-25

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia