



## **Technical data**

| Model No.                | T-100K         | Tank Capacity (L)           | 5.2 Steel Tank   |
|--------------------------|----------------|-----------------------------|--|
| Max. Pressure (kg/cm²)   | 100 (~ 98 bar) | Size of Discharge Nozzle    | 1/4  |
| Plunger Diameter (mm)    | 22             | Weight (kg)                 | 7.0  |
| Stroke (mm)              | 35             | Dimensions (L x H x W )(mm) | 370 x 300 x 210  |
| Suction Per Stroke (c.c) | 13             | Accessories                 | Pressure gauge 1/4PT<br>Ultra high pressure hose 1/4PF x 1m<br>Nipple 1/4" |

## T-100K Hydraulic Pressure Test Pump

Common used to check fluid pressure vessel, such as, cylinders, boiler, tubes pipe, etc.

Kyowa T-100K test pump an excellent choice to suit all pressure test application.

## Features:

- 1. High-precision stainless steel (SUS 304) ball value is applied as the value.
- 2. Value seat is replaceable with ease.
- 3. Water tank of rust-free plastic (P.P.) construction unchanging cleanliness.
- 4. The plunger packing used is standard product, O-ring No. P-22 which is available in local hardware dealers.
- 5. All fulcrum pins applied are made of stainless steel.
- 6. A full range of accessories are provided to permit on-the-spot job.
- 7. Matchless compact and light-weight design in the world.





+65 6296 7711



https://huphong.com.sg