



Main	
Range	PratiKa
Product or component type	Socket
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	3P + E
Network type	AC
Outlet standard	Industrial

Complementary

Mounting mode	Wall-mounted	
Plug, socket, control station shape	Angled	
[In] rated current	32 A	
[Ue] rated operational voltage	380415 V	
Network frequency	50/60 Hz	
Ground lug clockwise position	6 h	
Plug, socket material	Housing: self-extinguishing engineering polymer	
Contacts material	Pins: stainless steel Sleeves: nickel plated brass Springs: stainless steel	
Connections - terminals	Captive screws, completely loosened	
Cable cross section	2.510 mm²	
Cable outer diameter	11.521 mm	
Net weight	0.485 kg	
Base dimension	106 x 130 mm	
Height	130 mm	
Width	106 mm	
Depth	189 mm	
Colour	Grey (RAL 7035)	
Voltage colour	Red	

Environment

Standards	EN 60309-2 EN 60309-1	
IP degree of protection	IP44 conforming to IEC 60529	
IK degree of protection	IK08 conforming to EN 62262	
Fire resistance	850 °C conforming to IEC 60695-2-11	
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C	
Ambient air temperature for operation	35 °C (86400 s)	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.7 cm
Package 1 Width	14.8 cm
Package 1 Length	18.9 cm
Package 1 Weight	422.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	2
Package 2 Height	12.0 cm
Package 2 Width	21.5 cm
Package 2 Length	27.0 cm
Package 2 Weight	935.0 g
Unit Type of Package 3	S03
Number of Units in Package 3	6
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	3.292 kg

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	
Circularity Profile	No need of specific recycling operations	

Contractual warranty

144	10 11	
Warranty	18 months	