

# AP4424A

APC Netshelter Rack Automatic Transfer Switch, 2U, 32A, 230V, 2 IEC 309 IN, 16 C13, 2 C19 OUT, 50/60 Hz



## Overview

Lead time	Usually in Stock
-----------	------------------



## Main

Main Input Voltage	230 V AC 1 phase
Main Output Voltage	230 V AC 1 phase
Input Connection Type	IEC 60320 IEC 60309 32 A 2P + E IEC 60320
Number of rack unit	2U
Cable length	2.44 m
Number of cables	2
Provided equipment	Mounting hardware Rack mounting brackets

## Physical

Colour	Black
Height	8.8 cm
Width	43.2 cm
Depth	23.6 cm
Net weight	6.94 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Horizontal

## Input

Network frequency	50/60 Hz
Permissible voltage	207...253 V
Load capacity	7400 VA

## Output

Max current draw	32 A
Number of power socket outlets	18
Protection type	Circuit breaker

## Conformance

Product certifications	EN 55022 class A[RETURN]FCC part 15 class A
Standards	EN 55022 class A FCC part 15 class A

## Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21 cm
Package 1 Width	58.4 cm
Package 1 Length	35.6 cm
Package 1 Weight	9.43 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	20
Package 2 Height	120 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	201.2 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Lead free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------