




# Datasheet

**ENGLISH**

**146-4649**

## RS PRO NETWORK MINIATURE CAMERA(1080P)



### Feature

- Sony Exmor 2MP Image Sensor
- Triple Codec (H.264/MPEG4/MJPEG)
- Triple Stream
- Support Onvif latest version
- Support POE Cable
- True Day & Night
- Mega 3.6mm Fixed Lens

#### CAMERA SECTION

<b>IMAGE</b>	Image Sensor	Sony Exmor 2.07MP Image Sensor
	Scan System	Progressive Scan
	Total Pixels	2000(H)×1121(V) 2.24MegaPixles
	Effective Pixels	1984(H)×1105(V) 2.19MegaPixles
<b>Function</b>	Day & Night	Auto/Day(Color)/Night(BW)
	Privacy	Area On/Off (6 Programmable Zone)
	WDR	DWDR (1~5Step)
	3D DNR	ON / OFF
	Motion Detector	432 Zone (On/Off, 1~5Step)
	Elec. Shutter	Auto(1/30~1/10000), Suppress Rolling, Manual
	White Balance	Auto/Indoor/Outdoor/Fluorescent
	Ext. Video	VBS1.0Vp-p
<b>Lens</b>	Focal Length	3.6mm FIXED LENS
<b>IR LEDs</b>	IR LEDs	N/A
<b>Electrical</b>	Power Supply	DC12[V] ±10% / POE Current Max 750mA
<b>Environmental</b>	Operating Temp.	-10°C ~ +40°C
	Preservation Temp.	-20°C ~ +50°C
	Humidity	0% ~ 80%
<b>Mechanical</b>	Weight	Approx. 70g

#### NETWORK SECTION

<b>System</b>	OS	Embedded Linux
<b>Network</b>	Interface	RJ45 100/100 Base-T PoE
	Protocol	TCP/IP,UDP/IP,RTP,RTSP,RTCP,NTP, HTTP,DHCP,FTP,SMTP,DNS,DDNS
	Onvif	Ver2.4
	DDNS	iplinker.net
<b>Video</b>	Simultaneous Access	Max. 10 user
	Compress Format	H.264/MPEG4/MJPEG
	Resolution	1920×1080/1280×720/640×360/ 320×180
	Frame rate	5fps ~ 30fps @ all resolution
	Video Quality	H.264,MPEG4 : Bit rate Control MJPEG : Quality Level Control
	Streaming	Triple Stream (Stream1,2,3) RTP/RTSP, UnicastRTP, Multicast RTP
<b>Audio</b>	Compress Format	G.711 u-law
	Streaming	Two way
<b>Event</b>	Sensor In	1 (Digital Input)
	Alarm Out	1 (Digital Output, Open Collector)
	Manager	IE, Firefox, Safari, Opera
<b>Web Browser</b>	Viewer	IE over 10ver (Active-X)