



Benefits

- Perfect LED replacement for halogen lamps in applications where the faithful colour reproduction associated with natural light is crucial
- Offers perfect linear dimming which is compatible with most popular dimmers in the market
- Compact & powerful at 117lm/w

Application




Model	Item Description	W	PF	lm	lm/w	CRI	Beam	Life	Single Box (LxWxH)mm	Outer Box (LxWxH)mm	Packing Qty (PCS/CTN)
LG200130/dm-OPv00	SIGV1 A60 13W E27 FS 3000K DIM	13.0	0.7	1521	117	80	200°	25000	60*60*114	630*320*245	60
LG200130/dm-OPv00	SIGV1 A60 13W E27 FS 4000K DIM	13.0	0.7	1521	117	80	200°	25000	60*60*114	630*320*245	60
LG200130/dm-OPv00	SIGV1 A60 13W E27 FS 6500K DIM	13.0	0.7	1521	117	80	200°	25000	60*60*114	630*320*245	60

Application Conditions	
IP	IP20
Operating Temperature	-20~40°C
Application Temperature	25°C
Storage Environment	-25~50°C

Mechanical Properties	
Optical Material	PC
Housing Material	PBT
Finishing Colour	White

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC

Dimensional Drawing



LG200130/dm-OPv00