




125



AIR INJECTION

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



QUICK-RELEASE AIR FILTER

Facilitates cleaning and replacement of the air filter.



FELLING MARKS

Distinct felling marks for better felling precision.



FUEL PUMP

Fuel pump designed for easy starting.

Features

- Increased safety, inertia activated chain brake

Technical data

Cylinder displacement	40 cm ³ / 2.4 cu.inch
Power output	1.52 kW
Maximum power speed	9000 rpm
Fuel tank volume	0.25 lit / 8.45 fl oz
Fuel consumption	454 g/kWh
Idling speed	3000 rpm
Spark plug	TORCH CMR7H
Electrode gap	0.6 mm / 0.02 "
Torque, max.	1.73 Nm/8000 rpm
Oil tank volume	0.15 lit / 0.32 US pint
Oil pump type	Automatic
Equivalent vibration level (ahv, eq) front / rear handle	6.7/5.8 m/s ²
Sound pressure level at operators ear	99 dB(A)
Sound power level, guaranteed (LWA)	108 dB(A)
Chain pitch	3/8"
Chain speed at 133% of maximum engine power speed	1.15 m/s / 3.77 fts
Recommended bar length, min-max	40.64-45.72 cm / 16"-18"
Chain gauge	0.05 "
Weight (excl. cutting equipment)	4.6 kg / 10.1 lbs

ARTICLES

967 06 80-01 18" 3/8" - ID, MY, VT, PG, PH, IN, BT, LK

967 06 80-02 16" 3/8" - CN



HUSQVARNA DEALER: