

## FEATURES

- Material: Warp proof self-extinguishing UL approved PVC, 94V-0 flammability rating, M1 rating NF fire resistant test.
- Color: Black
- These devices are for routing of wires within devices in factory installations.
- Features parallel holes on both sidewalls to facilitate cutting in wire application.
- Special color, size, length upon request of reasonable quantity.

## RS PRO Wiring Duct

RS Stock No.: 2339182 2339183



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description ATTRIBUTE 1

- Material: Warp proof self-extinguishing UL approved PVC, 94V-0 flammability rating, M1 rating NF fire resistant test.
- Color: Black
- Vicat softening point: 86°C
- UL Test up to 50°C
- These devices are for routing of wires within devices in factory installations.
- Features parallel holes on both sidewalls to facilitate cutting in wire application.
- Special color, size, length upon request of reasonable quantity.
  - Regular wiring duct cover can be upgrade to NON-SLIP ones which improves tightness between duct and cover, benefits vertical installations, and improves effectiveness and avoid cover slip off.

## General Specifications

<b>Series</b>	Wiring Duct
<b>Type</b>	
<b>Colour</b>	Black
<b>Material</b>	PVC
<b>UV Resistant</b>	NO
<b>Minimum Operating Temperature</b>	0°C
<b>Maximum Operating Temperature</b>	Vicat softening point: 86°C, UL Test up to 50°C
<b>Fire Behaviour</b>	Self-Extinguishing
<b>Quantity</b>	2M

## Mechanical Specifications

Unit:mm

W x H (mm)	Slot	Wires to be Contained (16-14 AWG)	Length	Color
100x75	8	260 ~ 320 pcs	2M	Black
100x100	8	300 ~ 400 pcs	2M	

## Approvals

<b>Declarations</b>	
<b>Standards Met</b>	UL, CSA, CE, VDE, RoHS

## Similar Products

Stock No.	Brand	Product Name	Colour	Material

