

## **FEATURES**

- Operating temperature range is from - 60 °C to + 300 °C
- RoHS and REACH compliant
- Silicon free

# RS PRO TEE CONNECTOR COMPRESSION

RS Stock No.: 2312555



RS PROfessionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the

leading brands without paying a premium price.



### **Product Description**

The RS PRO tee connector compression is made up of brass.

The working pressures and working temperatures depend on which type of tube is used, for this reason, the values must be determined in accordance with the tube's features.

Hereunder, we specify the values of the maximum pressure advised for the fittings at a temperature of 20° C connected with copper tube, which has a thickness of 1 mm.

Here the tube size is 8 and corresponding maximum pressure advised is 133.6 bar.

#### **General Specifications**

Fitting Type	Tee
Material	Brass
Fitting Direction	Tee
Application	Compressed Air, Pneumatic Automation, Industrial water circuits, Inert Gases, Fluids, Steam Vacuum

#### **Mechanical Specifications**

Connection 1	M14 Metric Female	
Connection Gender 1	Female	
Thread Size 1	M14	
Thread Standard 1	Metric	
Connection 2	M14 Metric Female	
Connection Gender 2	Female	
Thread Size 2	M14	
Thread Standard 2	Metric	
Connection 3	M14 Metric Female	
Length	28.5mm	
Overall Length	57mm	
Wrench Size	12mm	



# **Operation Environment Specifications**

Temperature	Min.	Max.
	- 60 °C	+ 300 °C


# **Approvals**

Approvals RoHS and REACH compliant	
------------------------------------	--

## **Similar Products**

Parameters	2312553	2312555
Brand	RS PRO	RS PRO
Connection 1	M14 Metric Female	M14 Metric Female
Connection Gender 1	Female	Female
Thread Size 1	M14	M14
Thread Standard 1	Metric	Metric
Connection 2	M14 Metric Female	M14 Metric Female
Connection Gender 2	Female	Female
Thread Size 2	M14	M14
Thread Standard 2	Metric	Metric
Connection 3	M14 Metric Female	M14 Metric Female
Length	44mm	28.5mm
Overall Length	22mm	57mm
Wrench Size	8mm	12mm





Tube	L1	L2	СН	Pack
8	57	28.5	12	10