# Ceramic Disc Capacitors multicomp PRO





## **Specification Table**


Voltage (DC)	Capacitance (picofarads)	Tolerance	Temperature Characteristics	Temperature Coefficient	Operating Temperature	Part Number
1kV	100	±20%	SL	+100ppm, -750ppm	-55°C to +125°C	MCCC1KV101MSL
1kV	2200	±20%	Z5U	+22%, -56%	+10°C to +85°C	MCCC1KV222MZ5U
100V	10000	±5%	Y5P	±10%	-30°C to +85°C	MCCC100V103JY5P
100V	10000	±10%	Y5P	±10%	-30°C to +85°C	MCCC100V103KY5P
100V	100000	±10%	Y5P	±10%	-30°C to +85°C	MCCC100V104KY5P
100V	4700	±10%	Y5P	±10%	-30°C to +85°C	MCCC100V472KY5P
100V	47000	±10%	Y5P	±10%	-30°C to +85°C	MCCC100V473KY5P
200V	1000	±10%	Y5P	±10%	-30°C to +85°C	MCCC200V102KY5P
200V	10000	±10%	Y5P	±10%	-30°C to +85°C	MCCC200V103KY5P
250V	50000	±20%	Y5U	+22%, -56%	-30°C to +85°C	MCCC250V503MY5U
3kV	150	±20%	X7R	±15%	-55°C to +125°C	MCCC3KV151MX7R
50V	100000	±10%	Y5P	±10%	-30°C to +85°C	MCCC50V104KY5P
50V	22000	±10%	Y5P	±10%	-30°C to +85°C	MCCC50V223KY5P
50V	220000	±10%	Y5U	+22%, -56%	-30°C to +85°C	MCCC50V224KY5U
50V	47000	±10%	Y5P	±10%	-30°C to +85°C	MCCC50V473KY5P
600V	50000	±10%	Y5V	+22%, -82%	-30°C to +85°C	MCCC600V503MY5V
100V	100	±20%	SL	+100ppm, -750ppm	-55°C to +125°C	MCCC100V101JSL
1.5kV	22	±5%	NPO	±30ppm	-55°C to +125°C	MCCC1500V220JNPO
1.5kV	27	±5%	NPO	±30ppm	-55°C to +125°C	MCCC1500V270JNPO
50V	22	±5%	NPO	±30ppm	-55°C to +125°C	MCCC50V220JNPO



## Ceramic Disc Capacitors multicomp PRO



### **Part Number Explanation**



Temperature Characteristics	Temperature Coefficient	Operating Temperature	
SL	+100ppm, -750ppm	-55°C to +125°C	
NPO	± 30ppm	-55°C to +125°C	
X7R	± 15%	-55°C to +125°C	
Y5P	±10%	-30°C to +85°C	
Y5U	+22%, -56%	-30°C to +85°C	
Y5V	+22%, -82%	-30°C to +85°C	
Z5U	+22%, -56%	+10°C to +85°C	

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

