KB31TS_WE

Telephone outlet with shutter, Vivace, 1 gang, White





Main Range of product Vivace Range Vivace Device short name KB31 Product or component type Device presentation Complete mechanism Telephone socket type RJ11

White

Complementary

Number of gangs	1 gang	
Colour tint	White	
Connector type	M-110 keystone RJ45 connector	
Material	Polycarbonate: surround Polycarbonate: grid plate Polycarbonate: base	
Projecting depth	8 mm	
Device mounting	Flush	
Mounting support	Wall mounted	
Fixing center	60.3 mm	
Embedding depth	35 mm	
Connections - terminals	Clamp terminal	
Tightening torque	0.4 N.m	
Width	87 mm	
Height	87 mm	
Main colour tint	White	

Colour tint

Environment

Ambient air temperature for operation	-540 °C
Relative humidity	095 %
Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.2 cm	
Package 1 Width	8.6 cm	
Package 1 Length	8.6 cm	
Package 1 Weight	82.1 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	
Package 2 Height	15 cm	
Package 2 Width	19 cm	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or infability of these products for specific user applications. It is the doubt of any substitute for and is not to be used for determining suitability or infability of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or substitaires shall be responsible or liable for misuse of the information contained herein.

Package 2 Length	10 cm	
Package 2 Weight	890 g	
Unit Type of Package 3	CAR	
Number of Units in Package 3	100	
Package 3 Height	21 cm	
Package 3 Width	31.5 cm	
Package 3 Length	50 cm	
Package 3 Weight	8450 g	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

warranty 18 months	Warranty	18 months
--------------------	----------	-----------