

TECHNICAL DATA SHEET

WIRE CABLE SELF RETRACTING LIFELINE ARA GALVA



Product Description :

Resistant

- Self retracting lifeline with galvanized cable
- Housing highly resistant to shocks and friction
- Vertical use

Easy to use

- Carrying Handle
- Equipped with two swivels (one at the top, one at the bottom of the device) to follow the user's movements with complete freedom and avoid the risk of the cable being twisted

Reference	Length
EX301-06	6m

Certified to EN360

Technical information :

Wire cable	Galvanized steel Ø4.5mm, Breaking strength >12kN
Housing	Polymer
Termination (Top)	Removable twistlock connector, mounted on a swivel
Termination (Bottom)	Non-removable twistlock connector with swivel and fall indicator
Space clearance	Minimum 3m
Temperature of use	Temperature range : -30°C to +50°C
Use	Vertical use, angle till 40° from vertical
Max user weight	137kgs
Certification	EN360:2002

REGULATION OF March 19, 1993

PPE against falls from height are classified in category III (fatal risks):
 "[t]his personal protective equipment must have been subject, for less than twelve months at the time of its use, to the periodic general inspection provided for in Article R.233-42-2 of the [French] Labor Code"

For any information, please contact our team at
 +33 (0)5.45.78.83.85

EXYAN
 FALL PROTECTION EXPERT