# **RF Terminators**

# multicomp PRO

RoHS

**Compliant** 

### MP006798 - N Plug Terminator

### **Electrical**

• Frezuency Range : DC to 11GHz • Nominal Impendance :  $50\Omega$ • DC Resistance :  $50\Omega \pm 5\%$ • Power Rating : 1W

• VSWR : 1.22 Max. @ 6.1 GHz

1.3 Max. @ 11 GHz

#### **Materials**

Bodies : Brass Per JIS-C3604Center Contact : Brass Per JIS-C3604


Insulation : PTFE Per ASTM D1457 and ASTM D1710

#### Mechanical

Interface in Accordance with : MIL-STD-348A

### **Environmental**

• Operating Temperature Range -40°C to +70°C



Finishes and Others						
No	Description	Material	Finish			
1	Shell	Brass	White Bronze 80µ" Min.			
2	Center Contact	Brass	Gold 20µ" Min. Over Electronicss Nickel 50µ" Min.			
3	Gasket	Silicon	Red			
4	Chassis	Brass	White Bronze 80µ" Min.			
5	Washer	Brass	None			
6	Insulation	PTFE	None			
7	Body	Brass	White Bronze 80µ" Min.			
8	Resistor	1W - 50Ω	None			
9	Chassis	Brass	Gold 3μ" Min. Over Electronicss Nickel 50μ" Min.			

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



# **RF Terminators**



### MP006806 - SMA Straight Plug Terminator

### **Electrical**

• Frezuency Range : DC to 18GHz • Nominal Impendance :  $50\Omega$  • DC Resistance :  $50\Omega \pm 5\%$ 

Power Rating : 1W

• VSWR : 1.22 Max. @6.1 GHz

1.6 Max. @18 GHz

#### **Materials**

Bodies : Brass Per JIS-C3604Center Contact : Brass Per JIS-C3604


Insulation : PTFE Per ASTM D1457 and ASTM D1710

### Mechanical

Interface in Accordance with : MIL-STD-348A
Recommended Coupling Torque : 3 to 5 in-lbs

Environmental

Operating Temperature Range -40°C to +70°C



Finishes and Others						
No	Description	Material	Finish			
1	Shell	Brass	Electronics Nickel 100µ" Min.			
2	Gasket	Silicon	Red			
3	Insulation	PTFE	None			
4	Center Contact	Brass	Gold 50μ" Min. Over Electronicss Nickel 50μ" Min.			
5	Resistor	Metal Film	1W-50Ω			
6	Chassis	Brass	Gold 3µ" Min. Over Electronicss Nickel 50µ" Min.			
7	Washer	Stainless Steel	None			
8	Body	Brass	Gold 3µ" Min. Over Electronicss Nickel 50µ" Min.			

Dimensions: Millimetres

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



## **RF Terminators**



### **Part Number Table**

Description	Part Number
N Plug Terminator, 1W Power Rating	MP006798
Straight SMA Plug Terminator, 1W Power Rating	MP006806

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



Page <3> 14/06/21 V1.0