

Datasheet

RS Pro 2A Radial Non-Resettable Wire Ended Fuse, 250 V

RS Stock No: **767-5055**



Product Details

RS Pro radial non-resettable fuse withstands currents up to 2 A and voltages up to 250 V. It has thermoplastic body for added durability. This slow blow fuse forms a convenient and reliable solution to a vast array of application requirements.

Features and Benefits

- Slow blow fuse
- Base and cap in black thermoplastic
- Round pins in tin plated copper
- Vibration MIL-STD-202G
- Salt spray MIL-STD-202G
- Insulation resistance MIL-STD-202G
- Resistance to solder heat MIL-STD-202G
- Thermal shock MIL-STD-202G

**Specifications:**

| | |
|---|---|
| Body Height | 7.7 mm |
| Body Length | 8.35 mm |
| Body Material | Thermoplastic |
| Body Width | 4.3 mm |
| Breaking Capacity (at Maximum Voltage Rating) | 35 A at 250 V ac |
| Current Rating | 2 A |
| Lead Orientation | Radial |
| Maximum Operating Temperature | +125°C |
| Minimum Operating Temperature | -55°C |
| Voltage Rating | 250 V |
| Voltage Rating | 250 V |
| Wire Diameter | 0.62 mm |
| Wire Length | 22 mm |
| Wire Pitch | 5.08 mm |
| Fuse Type | Time Lag |
| Nominal Resistance | 0.0316 Ω |
| Standards Met | SEMKO, VDE, TUV, CSA, UL, CCC, KTL, PSE, RoHS |