

FEATURES

- UL approved Nylon 66, 94V-2
- Color: Natural, other special colors are available upon request.
- Press the tie into a pre-drilled hole and bind the cord by securing the tie.

RS PRO Push Mount Tie

RS Stock No.: 2243189



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

ATTRIBUTE 1

- Material: UL approved Nylon 66 , 94V-2.
- Color: Natural
- Press the tie into a pre-drilled hole and bind the cord by securing the tie.

General Specifications

Series	Push Mount Tie
Type	Non-Releasable
Colour	Natural
Material	Nylon 66
Finish	
Application	
Resistant To	
UV Resistant	No
Minimum Operating Temperature	-40°C
Maximum Operating Temperature	85°C
Fire Behaviour	Self-Extinguishing
Quantity	25

Mechanical Specifications

Length	112mm(4 3/8")
Width	2.5mm
Max. Bundle Dia.	25mm
Mounting Hole	4.6mm
Chassis Thickness	2.6mm
Tensile Strength	18lbs/8kgs
Thickness	1.1±0.25mm

Protection Category

IP Rating

Classification

eCl@ss (10.0.1)
UNSPSC (6.01)

Approvals

Declarations

Standards Met

UL, RoHS, SVHC, HF, ABS

Similar Products

Stock No.	Brand	Product Name	Colour	Material	Tensile strength
178-9501	RS	Push Mount Tie	Natural	Nylon66	50lbs/22kgs

