

V-205

Stick Welding
Power Source

Quick Specs

Industrial Applications

Petro/Chem Fabrication
Shipboard Installation/Repair
Mechanical Contractors
Mining
Process Piping

Power Voltage

1 Phase AC240V ±15%
50/60Hz

Input Current

22A/5.3kVA

Output Current

30-170A
Max. OCV: 65VDC

Output Voltage

28V

Duty Cycle

60%

Weight

5.5KG

Dimensions

D310×H330×W170MM

Portable. Professional. Rugged. Affordable.

The inverter V-205 offers much more than you would expect from a welder this size. Weighing in at just under 5.5kg the Inverter V-205 is no lightweight contender. It packs the full punch of a heavyweight professional that you can take to the most demanding job sites. It can operate from a portable generator.

FEATURES

- **Automatic Arc Force** minimizes electrode sticking in the puddle without compromising arc stability or increased spatter.
- **Automatic Hot Start** boosts the current during starting to make striking an arc easier.
- **Thermal overload protection with indicator light** helps prevent machine damage if the duty cycle is exceeded or airflow is blocked.
- Inverter-based, DC power source has a **simple-to-use operator interface** providing only the necessary controls in a compact machine.

PROCESSES

Stick (SMAW)



INCLUDED

V-205 Machine Only Includes:

- V-205
- 3M Stick electrode holder.
- 2M work cable and clamp.

INPUT



OUTPUT



AUSTCORP MANUFACTURING SDN. BHD.

NO. 8 & 10 PERSIARAN BATU GAJAH PERDANA 3

TAMAN BATU GAJAH PERDANA

31550 PUSING PERAK MALAYSIA

TEL: (605)3632 115 FAX: (605)3632 111

E-mail: austcorp@welding.com.my

WEB: www.welding.com.my



Welding Technology