

**! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Name of product** WEICON ST Resin  
Code-Nr. 104101

**1.2. Relevant identified uses of the substance or mixture and uses advised against  
Recommended intended purpose(s)**

2-Component Epoxy Resin - Resin Component

**1.3. Details of the supplier of the safety data sheet****Distributor**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster  
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

**Advice**

Produktsicherheit / Product-Safety-Department  
Phone : +49(0)251 / 9322 - 0  
Fax : +49(0)251 / 9322 - 244  
E-mail (competent person):  
msds@weicon.de

**1.4. Emergency telephone number**

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:  
++44 1865 407333 (English)  
TRANSPORT EMERGENCY CONTACT - UK, UAE, South  
Africa (24h): Tel: ++44 1865 407333 (English)

**Manufacturer**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

**1.4. Emergency telephone number**

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):  
Tel: ++49 69 222 25285 (Deutsch, Englisch)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315	
Eye Irrit. 2	H319	
Skin Sens. 1	H317	
Aquatic Chronic 2	H411	

**Hazard Statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

**2.2. Label elements**

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07



GHS09

**Signal word**

Warning

**Hazard Statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary Statements**

P102	Keep out of reach of children.
P261	Avoid breathing vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P501	Dispose of contents/container to hazardous or special waste collection point.

**Hazardous ingredients for labeling**reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )**Special rules for supplemental label elements for certain mixtures**

Contains epoxy constituents. May produce an allergic reaction.

**2.3. Other hazards****Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

**3.2. Mixtures****Description**

Epoxy resin compound containing mineral fillers.



Safety Data Sheet according to Regulation (EC)  
No. 1907/2006 (REACH)

Printed 05.08.2019  
revision 10.07.2018 (GB) Version 8.6

**WEICON ST Resin**

**Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25 - 50	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
9003-36-5	500-006-8	bisphenol f epoxy resin	1 - 25	Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411

**REACH**

CAS No	Name	REACH registration number
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	01-2119456619-26
9003-36-5	bisphenol f epoxy resin	01-2119454392-40

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

If threatening unconsciousness, position and transport in recovery position  
In case of breathing difficulties give oxygen.

**In case of inhalation**

Remove the casualty into fresh air and keep him immobile.  
In the event of symptoms refer for medical treatment.

**In case of skin contact**

In case of contact with skin wash off with soap and water.  
Consult a doctor if skin irritation persists.

**In case of eye contact**

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

**In case of ingestion**

Do not induce vomiting.  
Refer to medical treatment.  
If swallowed give water to drink.

**4.2. Most important symptoms and effects, both acute and delayed**

**Physician's information / possible symptoms**

skin irritation

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**! SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Foam  
Dry fire-extinguishing substance  
Carbon dioxide  
Water spray jet

**! Unsuitable extinguishing media**

Full water jet



---

**5.2. Special hazards arising from the substance or mixture**

In case of fire formation of dangerous gases possible.

Nitrogen oxides (NO<sub>x</sub>)  
Carbon monoxide (CO)  
Carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

**Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

**Additional information**

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

---

**! SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

**6.2. Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

**6.3. Methods and material for containment and cleaning up**

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

**6.4. Reference to other sections**

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

---

**! SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**! Advice on safe handling**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

**General protective measures**

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

**Hygiene measures**

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Pay attention to general rules of internal fire prevention.

**WEICON ST Resin****7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in closed original container.

**Advice on storage compatibility**

Do not store with acids or alkalis.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

**Further information on storage conditions**

Store closed container at cool and aired place.

Protect from heat and direct solar radiation.

Store in a dry place.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	8,33 mg/kg bw/day	DNEL long-term dermal (local)	
		8,33 mg/kg bw/day	DNEL long-term dermal (systemic)	
		12,25 mg/m3	DNEL long-term inhalative (systemic)	
9003-36-5	bisphenol f epoxy resin	29,39 mg/m3	DNEL long-term inhalative (systemic)	
		0,0083 mg/cm2	DNEL acute dermal, short-term (local)	
		104,15 mg/kg	DNEL long-term dermal (systemic)	

**PNEC**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	0,018 mg/l	PNEC aquatic, intermittent release	
		11 mg/kg	PNEC Secondary Poisoning	
		0,996 mg/kg	PNEC sediment, freshwater	
		10 mg/l	PNEC sewage treatment plant (STP)	
		0,0006 mg/l	PNEC aquatic, marine water	
		0,006 mg/l	PNEC aquatic, freshwater	
		0,0996 mg/kg	PNEC sediment, marine water	
9003-36-5	bisphenol f epoxy resin	11 mg/kg	PNEC Secondary Poisoning	
		0,0006 mg/l	PNEC aquatic, marine water	
		0,294 mg/kg	PNEC sediment, freshwater	

**DNEL-/PNEC-values (continued)**

CAS No	Substance name	Value	Code	Remark
		10 mg/l	PNEC sewage treatment plant (STP)	

**Additional advice**

The statutory local and national regulations have to be observed.

**8.2. Exposure controls****Respiratory protection**

If ventilation insufficient, wear respiratory protection.

Selection of the appropriate filter type depends on the quantity and chemicals handled at the workplace. Contact supplier of respiratory protective equipment or more information about filter properties.

**Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: natural rubber, 0,6mm; 480min; 60min;

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

**Eye protection**

tightly fitting goggles

**Other protection measures**

protective clothing

**Appropriate engineering controls**

Sufficient ventilation and exhaustion.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Appearance</b>	<b>Colour</b>	<b>Odour</b>
pasty	grey	mild

**Odour threshold**

not determined

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not determined				
<b>boiling point</b>	not determined				
<b>melting point</b>	not determined				
<b>Flash point</b>	> 100 °C				
<b>Vapourisation rate</b>	not determined				
<b>Flammable (solid)</b>	not determined				
<b>Flammability (gas)</b>	not determined				
<b>Ignition temperature</b>	not determined				

**WEICON ST Resin**

	Value	Temperature	at	Method	Remark
<b>Self ignition temperature</b>	not applicable				
<b>Lower explosion limit</b>	not determined				
<b>Upper explosion limit</b>	not determined				
<b>Vapour pressure</b>	not determined				
<b>Relative density</b>	ca. 1,6 g/cm <sup>3</sup>	20 °C			
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>					insoluble
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity</b>	1000000 mPa*s	25 °C			
<b>Oxidising properties</b>	No information available.				
<b>Explosive properties</b>	no				
<b>9.2. Other information</b>	No information available.				

**! SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

Reactions with acids, alkalies and oxidising agents.

**10.4. Conditions to avoid**

Keep away from heat.

**10.5. Incompatible materials****! Substances to avoid**

Alkali (lye)

Acid

Oxidising agent

**10.6. Hazardous decomposition products**

Gases/vapours, toxic

Carbon monoxide and carbon dioxide.

Nitrous oxides (NO<sub>x</sub>)

**Thermal decomposition**

Remark No decomposition if used as directed.

**! SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	11400 mg/kg	rat		CAS: 25068-38-6
<b>LD50 acute dermal</b>	> 20 ml/kg	rabbit		CAS: 25068-38-6
<b>Skin irritation</b>	irritant			
<b>Eye irritation</b>	irritant			
<b>Skin sensitization</b>	sensitizing			

**Experiences made from practice**

Sensitization through skin contact possible.

Irritates eyes and skin.

**! Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from products of similar composition.

**SECTION 12: Ecological information****12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
<b>Daphnia</b>	LC50 > 100 mg/l (96 h)	Daphnia magna		CAS: 9003-36-5

**12.2. Persistence and degradability**

	Elimination rate	Method of analysis	Method	Validation
<b>Biological degradability</b>				not degradable

**12.3. Bioaccumulative potential**

minimum bioaccumulative potential

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects****General regulation**

Toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.





The ecotoxic effect of the product has not been tested. The information on this was derived from products of similar structure or composition.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Recommendations for the product

Remove in accordance with local official regulations.

#### Recommendations for packaging

Empty containers can be deposited after cleaning in accordance with the local waste regulations.

#### General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

## SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	3082	3082	3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy-Harz)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy-resin)	Environmentally hazardous substance, liquid, n.o.s. (Epoxy-resin)
14.3. Transport hazard class(es)	9	9	9
14.4. Packing group	III	III	III
14.5. Environmental hazards	Yes	Yes	Yes

### 14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

#### Land and inland navigation transport ADR/RID

Hazard label(s) 9

tunnel restriction code E

Classification code M6

## ! SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### VOC standard

VOC content 0 %

### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



---

## **! SECTION 16: Other information**

### **! Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

### **Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.5

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.