

FX200-3-ZGSM-3-GRG

ZGSM LED Signal Heads for Road Signal Systems



Characteristics

- Ⓢ Utilizing imported LED chip, long lifespan.
- Ⓢ Using constant current driver, working voltage100-240VAC, low power
- Ⓢ Novel structure and beautiful appearance, using inflaming retarding and UV-proof housing material.
- Ⓢ Long visible distance, symmetrical light distribution.
- Ⓢ Multi-ply sealed water resistant, IP rating:>IP54.
- Ⓢ In accordance with GB/14887-2011 and relevant International standard.
- Ⓢ Visible distance: >500M.
- Ⓢ Working humidity: ≤95%
- Ⓢ LED Driver: Constant current driver (Efficiency>85% PF>0.85).

Ⓢ Main Technology Index

Model	Light Color	LED Qty	Light Intensity (mcd)	Wavelength (nm)	Visual Angle	Power Consumption (W)	Operating Temperature (°C)	Working voltage	Housing material	Dimension
FX200-3-ZGSM-3-GRG	G	64	8000~13000	500±5	<30°	< 5W	-40~+75	100-240VAC 50/60Hz	PC	750 x250 x160 mm 29.5 x9.8 x6.3 inches
	R	96	5000~7000	625±5		< 5W				
	G	64	8000~13000	500±5		< 5W				

Ⓢ Product Packing

Model	Qty	Packing Dimension	Gross Weight	Fixture Weight (single)	Packing material	Packing Volume
FX200-3-ZGSM-3-GRG	2	770 x390 x290 mm 30.3 x15.4 x11.4 inches	16.5 kg /36.4 lbs	7.6 kg /16.8 lbs	carton, foam	0.09 m³

CE  RoHS