

Datasheet

LCIS Relay Module

RS Stock number 888-6798



Identification

Type

LCIS-RGA24DC-S-1U

Part-No.

8886798

Input

Input voltage range	19.2 V – 30.0 V
Nominal voltage	DC 24 V
Rated frequency	50–60 Hz
Rated current	11.0 mA
Interrupting voltage	< 2.4 V
Protection device	Reverse- / overload diode
Max. length of connecting lead	DC 1000 m / AC 500 m
Status Indication	LED green

Load Side


Contact type	1 change over contact
Min. switching voltage	AC/DC 17 V
Max. switching voltage	AC/DC 250 V
Min. switching current	AC/DC 5 mA
Max. switching current	AC/DC 6 A
Switching capacity AC 15	3 A
Switching capacity DC 13	at 24 V: 1 A, at 125 V: 200 mA, at 250 V: 100 mA
Max. switching capacity	1500 VA
Contact material	AgSnO2

Mechanical service life	> 5 × 10 ⁷ operations
Switch-on delay	5 ms
Switch-off delay	4 ms
Clearance/creep. dist. (control/load side)	>5.5mm


**General**

Housing material	PA 6.6 (UL 94 V-0)
Protection class	IP 20
Field installation	rail TS 35 (EN 60175)
Insulation voltage input/output	4.0 kVeff
Safe isolation	yes
Rated insulation voltage (EN 50178)	300 V
Operation temperature range	-25 °C – 60 °C
Storage temperature range	-40 °C – 80 °C
Dimensions (w × h × d)	6.2 × 93.0 × 73.0 mm
Weight (kg/piece)	0.035
Approvals	UL, CSA, GL in preparation
Termination	Screw terminal: solid 0.25 – 2.0 mm ² / AWG 20 – 14 fine stranded with ferrule 0.25 – 1.5 mm ² / AWG 20 – 16 Stripping length: 8 mm Screw driver: 3.5 x 0.5 mm
Installation position	Optional

Dimensions



PIN assignment



Accessories

Tag holder (quantity 200)

Color
white (5×5 mm)

Article number
8886956

Type **PU**
LCIS-ZB-BZS-white- 1
00

Tag holder (quantity 120)

white (12×6 mm)

8886950

LCOS-ZB-BZS-whi- 1
te-12/6

Comments

Hard gold-plated contacts: So that the gold layer is not damaged, the specified values are not permitted to be exceeded. At higher switching capacity, the gold layer vaporizes. The deposition in the housing can lead to sparkovers between the coil and contact.