

Product data sheet

Characteristics

EPDU1232S

Easy Rack PDU, Switched, 0U, 3 Phase, 22kW, 230V, 32A, 18 C13 and 6 C19 outlets, IEC60309 3P + N + PE inlet



Overview

Lead time	Usually in Stock
-----------	------------------



Main

Colour	Black
PDU type	Switched

Complementary

Main Input Voltage	400 V 3 phases
Height	1794 mm
Width	55 mm
Main Output Voltage	230 V
Depth	62 mm
Net weight	8.17 kg
Mounting location	Side
Input Connection Type	IEC 60309 32 A 3P + N + PE
Mounting position	Vertical
Input current limits	32 A
Load capacity	22 kW
Network frequency	50/60 Hz
Plug standard	IEC 60309
Number of power socket outlets	18 IEC 60320 C13 6 IEC 60320 C19

Environment

Product certifications	CE[RETURN]EAC[RETURN]RCM[RETURN]TÜV
Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...3000 m
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1950 mm
Package 1 Width	160 mm
Package 1 Length	110 mm
Package 1 Weight	9.45 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------