



1.0 ELECTRICAL

- 1.1 FREQUENCY RANGE: DC-3 GHz
- 1.2 NOMINAL IMPEDANCE: 75 OHMS
- 1.3 WORKING VOLTAGE: 500 VOLTS MAX.
- 1.4 PROOF VOLTAGE: 1000 VOLTS
- 1.5 VSWR: 1.3 MAX.

2.0 MATERIALS

- 2.1 BODIES: BRASS PER JIS-C3604
- 2.2 CENTER CONTACT: BRASS PER JIS-C3604
- 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710

3.0 FINISHES AND OTHERS

- 3.1 SEE BELOW TABLE FOR DETAILS.

4.0 ENVIRONMENTAL

- 4.1 OPERATING TEMPERATURE RANGE: -40° C TO +85° C

APPROVED by _____ DATE: _____

6	NUT	BRASS	1	NICKEL 100μ" MIN.
5	CHASSIS	BRASS	1	NICKEL 100μ" MIN.
4	INSULATION II	TEFLON	1	NONE
3	CENTER CONTACT	BRASS	1	GOLD
2	INSULATION I	TEFLON	1	NONE
1	BODY	BRASS	1	NICKEL 100μ" MIN.
NO	DESCRIPTION	MATERIAL	Q'TY	FINISH



DESCRIPTION		BNC JACK - F PLUG ADAPTER			
製圖	DRAWN	TOLERANCE		品名	13-48-2 T.G.N
檢圖	CHECK	X	±0.2	TITLE	\ROHS COMPLIANT (750)
認定	APPROVAL	.XX	±0.1	單位	mm(in)
		.XXX	±0.05	SCALE	4:1
		ANGLE	±5°	比例	4:1
				DWG.NO.	13-0156
				DATE	08.28.08
				版次	A-0
				REV.	A-0