# Eaton BK/GMA-250-R

## Catalog Number: BK/GMA-250-R

Eaton GMA Series Fast-acting fuse 0.250A, 250 Vac, 32 Vdc (self certified), BK-GMA-250-R

# BUS

### General specifications

**RoHS** Compliant

Product Name	Catalog Number
Eaton Bussmann series GMA fast-acting	g BK/GMA-250-R
fuse	UPC
	051712647274
	051712047274
EAN	Product Length/Depth
5027590254618	20 mm
Deciver Lleight	Droduct Width
Product Height	Product Width
5 mm	5 mm
Product Weight	Warranty
0.002 kg	Not Applicable
Compliances	
CE Marked	



### **Product specifications**

### **Fuse indicator**

Non-indicating

### Interrupt rating

35 AIC at 250 Vac 10 kAIC at 125 Vac

### Туре

Electronic

Used with

out axial leads

Connection Ferrule end x ferrule end

### Response time

60 min at 135%, 2 min at 200%

### Quantity

100

### Material

Silver-plated brass endcap construction Glass tube

Voltage rating 250 Vac, 32 Vdc (self certified)

Application Electronic circuits

### **Amperage Rating**

0.250A



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2023 Eaton. All Rights property of their respective Reserved.

Eaton is a registered trademark.

All other trademarks are

owners.

### Resources

Specifications and datasheets

Eaton GMA time delay glass tube fuses data sheet

Eaton Specification Sheet - BK/GMA-250-R

Eaton.com/socialmedia

•

 $\mathbb{X}$ 

in