



Note:

- Maximum Insertion loss = 0.3dB
- Attenuation (dB/km): (1310/1550nm), (0.38/0.24)
- Primary Buffer Diameter = 0.25mm
- Components to be ROHS compliant
- Cable material to be LSZH
- Tolerances:  
 L -0/+100 (for L<0.5m)  
 L -0/+150 (for 0.5m>L<5m)  
 L -0/+200 (for L>5m)

ITEM NO.	PART NUMBER	QTY.
1	LC White Boot	2
2	Yellow Heat Shrink	2
3	Serial Number Label	1
4	LC Simplex Single Mode Connector (blue)	2
5	2mm OD Yellow Simplex Single Mode Cable	1



		UNLESS OTHERWISE SPECIFIED:	NAME	DATE	TITLE: <b>LC-LC Single Mode Simplex Patchcord</b>	
		DIMENSIONS ARE IN mm	DRAWN	A Hellyer		27/03/2006
		TOLERANCES: FRACTIONAL ±	CHECKED	S Harvey		27/03/2006
		ANGULAR: MACH ± BEND ±	ENG APPR.	Yes		27/03/2006
		TWO PLACE DECIMAL ± THREE PLACE DECIMAL ±	MFG APPR.			
		INTERPRET GEOMETRIC TOLERANCING PER:	Q.A.			
		MATERIAL	COMMENTS:			
		FINISH	Standard Configuration			
NEXT ASSY	USED ON				SIZE <b>A</b> DWG. NO. 060327-3 REV 1	
APPLICATION		DO NOT SCALE DRAWING			SCALE: NTS WEIGHT: SHEET 1 OF 1	