

MMCX Straight Plug

multicomp^{PRO}


RoHS
Compliant



Specifications

Frequency Range	: 6GHz
Nominal Impedance	: 50Ω
Coaxial Cable Types	: RG174
Bodies	: Brass per JIS-C3604 Beryllium copper per ASTM B196 UNS C17300
Centre Contact	: Brass per JIS-C3604
Insulation	: PTFE per ASTM D1457 and ASTM D1710
Crimp Ferrule	: Brass per JIS-C2700
Connector interface per BS EN 122340	
Part to be clean and free of burrs	

Diagram



No.	Description	Material	Finish
1	Washer	Beryllium Copper	Gold 3μ" Min.
2	Body	Brass	
3	Insulation	PTFE	None
4	Chassis	Brass	Gold 3μ" Min.
5	Centre Contact		Gold 30μ" Min.
6	Crimp Ferrule		Gold

Part Number Table

Description	Part Number
Straight Plug, Crimp, 50Ω, RG174, Beryllium Copper	MP-37-01L-5-TGG

Dimensions : Millimetres (Inches)

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp^{PRO}