



| 6 | Terminals | Brass | Silver Ptd. | 6 |
|-----|--------------|----------|-------------|------|
| 5 | Housing | ABS | | 1 |
| 4 | "T" Holder | Steel | Nickel Ptd. | 1 |
| 3 | Setscrew | Steel | Nickel Ptd. | 1 |
| 2 | Strain Boot | PVC | | 1 |
| 1 | Shield Cover | Zn Alloy | Nickel Ptd. | 1 |
| No. | Description | Material | Treat | Q'ty |

Specifications rating :

100V AC 4A MAX

contact resistance :

pins-30mΩ MAX; shell-50mΩ MAX

insulation resistance :

MIN 100 MEGΩ @500V DC

voltage withstand :

250V AC R.M.S. for 1 minute

| | | | | | | | | | | | | |
|-----------------|--------------------------|----------------|--|--|---------------------------|--------|---------------|-------|-----------------|-----------|------------------|------------|
| 品名: ITEM : | 6P DIN CABLE PLUG | | | | 一般公差 | SHEET: | 單位: unit: | mm | 日期: date: | '08/03/08 | 繪圖: drwn by: | DanielShyr |
| 料號: PART NO. | 491150 | 圖號: DRW NO. | | | .X +/-0.25 .XX +/-0.10 | | 比例: scale: | 3 : 2 | 版本: version: | V. 2.0 | 核准: aprld by: | SkyShyr |