

FEATURES

- Pre-punched
- Quick and easy install
- Clean black finish
- Up to 85°C operating temperature
- Wipe clean
- Slotted panel trunking for efficient cable management
- Made from PVC (polyvinyl chloride)

RS PRO Black Slotted Panel Trunking - Closed Slot, W25 mm x D30mm, L2m, PVC

RS Stock No.: 301-2084



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

RS PRO closed slot industrial trunking comes in black PVC, giving that clean modern finish to any work area. The pre-punched flat back allows you to organise your cables fixing them to the area the trunking will be applied to. Featuring a clip-on lid, allowing for a simple yet effective installation and secure cable organisation, whilst also allowing for quick and easy cable access. Our trunking is a box shape with a maximum operating temperature of 85°C, ideal for all of your cable and accessories management needs whilst providing that perfect finish.

General Specifications

Trunking/Chain Type	Slotted Panel Trunking
Material	PVC
Colour	Black
Fire Behaviour	Fireproof
Applications	Offices and indoor work spaces, at various lengths, Electrical workshops, Schools, Hospitals, Hotels and anywhere with customers or staff walking amongst cables

Mechanical Specifications

Length	2m
Width	25mm
Depth	30mm
Slot Type	Closed
Minimum Bend Radius	35mm

Operation Environment Specifications

Operating Temperature Range	-50°C to 60°C
Maximum Service Temperature	60°C

Approvals

Standards Met	CSA 82854, UL 94 V-2 Listed, IPX4
----------------------	-----------------------------------

Datasheet

COMPACT DATA TRUNKING

MATERIAL

Unplasticised PVC RAU1309

Fire rating

Tested to BSEN 50085 2-1: 2006 (Reaction to fire)
UL flammability classification: V0 at 1.5 and 3.0mm

External dimensions

Nominal	140mm height x 50mm depth
Actual	139mm height x 50mm depth

Minimum bend radius

35mm

Variable corners

Adjustable + / - 5°

Standard colours

White	RAL 9003
Grey (main lid only)	RAL 7012

Approx. weight assembled

1.5 Kg / mt

Cross section area

Top and bottom compartment 980mm² each

Classification according to BSEN 50085-2-1: 2006

- Non flame propagating
- With electrical insulation characteristics
- With high protection outside and inside
- Cable trunking systems for impact 5J
- Minimum installation and application temperature -5°C
- Maximum application temperature 60°C

Protection against the ingress of solid objects

IPX4 according to BSEN 60592: 1992

Total current maximum capacity of circuits inside trunking

120 A @ 230 V

Maximum socket depth

42mm with adjustable socket box