

Datasheet

RS Pro Star Delta Single Time Delay Relay, Screw, 3 → 120 s, SPNO, 2 Contacts, SP, 115 V ac

RS Stock No: **896-6835**



Product Details

RS Pro star delta single time delay relay is suitable for total electrical isolation. The timer is compact in size and suitable for DIN Rail mounting. It comes with a terminal screw type and has a time range of 3 to 120 s. It has SPNO, SN contact and switch configuration with 2 contacts and supply voltage of 115 V ac.

Features and Benefits

- 17.5 mm wide
- Star delta timing function
- DIN rail mounting
- Integrated dual voltage
- 0.3 s to 30 hours timing range
- LED indication for power and relay status
- IP20 (terminals), IP40 (enclosure) protection

**Specifications:**

Number of Timer Functions	Single
Power Supply	External
Switch Configuration	SP
Time Increment	Seconds
Depth	58.5 mm
Length	17.5 mm
Maximum Operating Temperature	+55°C
Minimum Operating Temperature	-10°C
Number of Contacts	2
Width	90 mm
Contact Configuration	NO (Delta), NO (Star)
Current Maximum	5 A
Current Minimum	0.1 A
Maximum Voltage	24 V ac/dc, 240 V ac
Mode of Operation	Star Delta
Mounting Type	DIN Rail
Supply Voltage	115 V ac
Terminal Type	Screw
Time Delay	150 ms
Time Range	3 to 120 s
IP Rating	IP20, IP40