

FEATURES

- Ideal for general purpose use. Contacts are polarised to ensure correct connection
- Miniature connector size
- ANSI colour coded
- The American National Standards Institute (**ANSI**) coordinates U.S. standards with international standards so that American products can be used worldwide.

RS PRO Miniature Thermocouple Connector Plug AM-E-M Type E ANSI

RS Stock No.: 769-1098



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

With flat pins to suit thermocouple type and ideal for general purpose use, all contacts are polarised to ensure correct connection. These connectors will accept thermocouple cable up to 4mm in diameter.

General Specifications

General Description	Ideal for general purpose use. Contacts are polarised to ensure correct connection.
----------------------------	---

Specifications

Thermocouple Type	E ANSI
Connector Type	Plug
Connector Size	Miniature
Colour	Violet
Max. Temperature	220°C
Pins	Flat Pins
+Positive Contact	Nickel Chromium
-Negative Contact	Copper Nickel

Approvals


RoHS Compliant	Yes
Standards Met	BS EN 50212:1997. RoHS

Thermocouple Connectors Product Guide

A comprehensive family of miniature and standard Thermocouple Connectors, accessories, panels, terminal and barrier blocks. Available in IEC, ANSI & JIS colour specifications.























[Click below to view:](#)

[RS Pro Thermocouple Connector Selection Guide](#)



Miniature in-line Plug
(dimensions in mm)

RS Components is a leading provider for Automation and Control Gear, below is a selection of best selling products:

<p style="text-align: center;">rspro.com</p> <div style="text-align: center;"> </div> <p style="text-align: center;">Temperature. It matters</p>	<div style="border: 1px solid red; padding: 5px; margin-bottom: 10px;"> <p style="text-align: right;">Best Sellers </p> </div> <p style="text-align: center;">Calibration</p> <p>Whether it's existing equipment or a new purchase, you need to have confidence in the accuracy of your measurements.</p> <p>That's where our calibration service can help.</p> <p>Purchase new products with confidence.</p> <p>A certificated calibrated sensor straight out of the box, ready to use.</p> <div style="display: flex; justify-content: space-around; margin-top: 10px;">  <div style="font-size: 0.8em;"> <p>ANSI SYSCAL Type K Mineral Insulated Thermocouple RS 181-7296</p> </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 10px;">  <div style="font-size: 0.8em;"> <p>IEC SYSCAL Type K Mineral Insulated Thermocouple RS 181-7288</p> </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 10px;">  <div style="font-size: 0.8em;"> <p>IEC SYSCAL Type J Mineral Insulated Thermocouple RS 181-7305</p> </div> </div> <div style="border: 1px solid red; padding: 5px; margin-top: 10px;"> <p style="text-align: right;">Best Sellers </p> </div> <div style="display: flex; justify-content: space-around; margin-top: 10px;">  <div style="font-size: 0.8em;"> <p>PT1000 Thin Film Detector RS 362-9907 Allied 70643582</p> </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 10px;">  <div style="font-size: 0.8em;"> <p>PT100 Wire Wound Detector RS 611-7839 Allied 70646151</p> </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 10px;">  <div style="font-size: 0.8em;"> <p>PT100 Wire Wound Detector RS 362-9799 Allied 70643577</p> </div> </div>
<div style="border: 1px solid red; padding: 5px; margin-bottom: 10px;"> <p style="text-align: right;">Best Sellers </p> </div> <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 30%;">  <p>Exposed Junction Thermocouples</p> <p>Including exposed junctions with fitted or moulded miniature plug and insulated leads, ideal for test and development applications. 1, 2, 3, 5 & 10m lengths available in IEC or ANSI colours.</p> </div> <div style="width: 65%;"> <div style="display: flex; justify-content: space-between; margin-bottom: 10px;">  <div style="font-size: 0.8em;"> <p>ANSI Type K Exposed Junction RS 814-0134 Allied 70656459</p> </div> </div> <div style="display: flex; justify-content: space-between; margin-bottom: 10px;">  <div style="font-size: 0.8em;"> <p>ANSI Type K High Temp Exposed Junction RS 131-4749 Allied 71080908</p> </div> </div> <div style="display: flex; justify-content: space-between;">  <div style="font-size: 0.8em;"> <p>IEC Type K Exposed Junction RS 363-0250 Allied 70643600</p> </div> </div> </div> </div>	<div style="border: 1px solid red; padding: 5px; margin-bottom: 10px;"> <p style="text-align: right;">Best Sellers </p> </div> <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 30%;">  <p>Fabricated and Specialist Thermocouples</p> <p>Styles include; Magnet, Washer, Nozzle, Leaf, Bayonet & Bolt thermocouple. Various lengths and calibration types available.</p> </div> <div style="width: 65%;"> <div style="display: flex; justify-content: space-between; margin-bottom: 10px;">  <div style="font-size: 0.8em;"> <p>Magnet Thermocouple RS 762-1115 Allied 70651739</p> </div> </div> <div style="display: flex; justify-content: space-between; margin-bottom: 10px;">  <div style="font-size: 0.8em;"> <p>Heavy Duty Thermocouple RS 762-1128 Allied 70651743</p> </div> </div> <div style="display: flex; justify-content: space-between;">  <div style="font-size: 0.8em;"> <p>Rubber Patch Thermocouple RS 290-5036 Allied 70642886</p> </div> </div> </div> </div>
<div style="border: 1px solid red; padding: 5px; margin-bottom: 10px;"> <p style="text-align: right;">Best Sellers </p> </div> <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 30%;">  <p>Thermocouple & PRT Cable</p> <p>Thermocouple cables are available in IEC or ANSI colour codes. Insulation types include PFA, PTFE, PVC & Fibreglass. Available spool lengths include 10, 25, 50, 100 and 200m.</p> </div> <div style="width: 65%;"> <div style="display: flex; justify-content: space-between; margin-bottom: 10px;">  <div style="font-size: 0.8em;"> <p>IEC PVC Insulated Flat Pair RS 219-4573 Allied 70641630</p> </div> </div> <div style="display: flex; justify-content: space-between; margin-bottom: 10px;">  <div style="font-size: 0.8em;"> <p>ANSI PFA Insulated Twin Twisted RS 814-0030 Allied 70656106</p> </div> </div> <div style="display: flex; justify-content: space-between;">  <div style="font-size: 0.8em;"> <p>IEC Glassfibre Insulated Flat Pair RS 236-3836 Allied 70641730</p> </div> </div> </div> </div>	<div style="border: 1px solid red; padding: 5px; margin-bottom: 10px;"> <p style="text-align: right;">Best Sellers </p> </div> <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 30%;">  <p>Thermocouple Connectors</p> <p>Range of miniature or standard thermocouple connectors. Available in thermocouple types K, J, T, E, N, RS, B, and copper. IEC, ANSI & JIS colour codes available.</p> </div> <div style="width: 65%;"> <div style="display: flex; justify-content: space-between; margin-bottom: 10px;">  <div style="font-size: 0.8em;"> <p>IEC Thermocouple Plug RS 455-9764 Allied 70644391</p> </div> </div> <div style="display: flex; justify-content: space-between; margin-bottom: 10px;">  <div style="font-size: 0.8em;"> <p>ANSI Thermocouple Socket RS 769-1127 Allied 70652125</p> </div> </div> <div style="display: flex; justify-content: space-between;">  <div style="font-size: 0.8em;"> <p>IEC Thermocouple PCB Socket RS 381-7570 Allied 70643749</p> </div> </div> </div> </div>

RS Components is a leading provider for Automation and Control Gear, below is a selection of best selling products:

 <p>Mineral Insulated Thermocouples</p> <p>Available in various calibration types with a variety of terminations. These include; Thermocouple plugs, Terminal heads and Thermocouple cable</p>	<p>Best Sellers </p> <p>IEC Thermocouple with PTFE Cable RS 397-1236 Allied 70643843</p> <p>IEC Thermocouple with Mini Plug RS 397-1488 Allied 70643863</p> <p>ANSI Thermocouple with PFA Cable RS 847-1019 Allied 70658112</p>	<p>NEW PRODUCTS </p>  <p>NEW PRODUCTS</p> <p>RS PRO, the own brand of RS Components, offers an unbeatable range of products across all industries with quality you can trust.</p> <p>New products are constantly added to improve the offering of our product range.</p> <p>Brake Pad Temp Sensor RS 200-0601 Allied 72173869</p> <p>RTD Temp Sensor Hirschmann Style RS 200-0594 Allied 72173862</p> <p>Washer Thermocouple RS 200-0616 Allied 72173882</p>
 <p>Sensors with Industrial Terminal Heads</p> <p>Industrial sensors housed in a stainless steel sheath and terminal head protection to IP67. Available as a thermocouple or Pt100.</p>	<p>Best Sellers </p> <p>Type K 300mm Long RS 787-7829 Allied 70653306</p> <p>Type K 200mm Long RS 787-7816 Allied 70653303</p> <p>Type K 100mm Long RS 787-7804 Allied 70653235</p>	<p>www.rspro.com</p>  <p>www.alliedelec.com</p>
 <p>L60 Fine Wire Thermocouple Welder</p> <p>The Thermocouple Welder is a compact, simple-to-use instrument designed for thermocouple and fine wire welding. Supplied with foot switch, spare electrodes, pliers & safety glasses, impact clip and pen plate.</p>	<p>Best Sellers </p>  <p>L60 Fine Wire Thermocouple Welder RS 363-0351 Allied 70825788</p> 	