

H07RN-F rubber-sheathed cable, harmonized type

Part no.	No. cores x cross-sec. mm ²	Outer Ø min. - max. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.	Part no.	No. cores x cross-sec. mm ²	Outer Ø min. - max. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
37029	3 G 2,5	10,9 - 14,0	72,0	235,0	14	37056	4 G 120	53,0 - 66,0	4608,0	6830,0	4/0
37030	3 G 4	12,7 - 16,2	115,0	320,0	12	37057	4 G 150	58,0 - 73,0	5760,0	8320,0	300 kcmil
37031	3 G 6	14,1 - 18,0	173,0	420,0	10	37058	4 G 185	64,0 - 80,0	7104,0	9800,0	350 kcmil
37032	3 G 10	19,1 - 24,2	288,0	810,0	8	37059	4 G 240	72,0 - 91,0	9216,0	12100,0	500 kcmil
37033	3 G 16	21,8 - 27,6	461,0	1050,0	6	37060	4 G 300	80,0 - 101,0	11520,0	15200,0	600 kcmil
37034	3 G 25	26,1 - 33,0	720,0	1250,0	4	37061	5 G 1,5	11,2 - 14,4	72,0	240,0	16
37035	3 G 35	29,3 - 37,1	1008,0	1900,0	2	37062	5 G 2,5	13,3 - 17,0	120,0	345,0	14
37036	3 G 50	34,1 - 42,9	1440,0	2600,0	1	37063	5 G 4	15,6 - 19,9	192,0	485,0	12
37037	3 G 70	38,4 - 48,3	2016,0	3400,0	2/0	37064	5 G 6	17,5 - 22,2	288,0	650,0	10
37038	3 G 95	43,3 - 54,0	2736,0	4450,0	3/0	37065	5 G 10	22,9 - 29,1	480,0	1200,0	8
37039	3 G 120	47,4 - 60,0	3456,0	5180,0	4/0	37066	5 G 16	26,4 - 33,3	768,0	1550,0	6
37040	3 G 150	52,0 - 66,0	4320,0	6500,0	300 kcmil	37067	5 G 25	32,0 - 40,4	1200,0	2250,0	4
37041	3 G 185	57,0 - 72,0	5328,0	7860,0	350 kcmil	37068	5 G 35	35,7 - 45,1	1680,0	2750,0	2
37042	3 G 240	65,0 - 82,0	6912,0	10224,0	500 kcmil	37091	5 G 50	41,8 - 53,0	2400,0	3950,0	1
37043	3 G 300	72,0 - 90,0	8640,0	12620,0	600 kcmil	37154	5 G 70	47,5 - 60,0	3360,0	4740,0	2/0
37044	4 G 1	9,2 - 11,9	38,0	150,0	18	34090	5 G 95	54,0 - 67,0	4560,0	6600,0	3/0
37045	4 G 1,5	10,2 - 13,1	58,0	200,0	16	34349	5 G 120	58,0 - 73,0	5760,0	8180,0	4/0
37046	4 G 2,5	12,1 - 15,5	96,0	290,0	14	34127	5 G 150	64,0 - 80,0	7200,0	10600,0	300 kcmil
37047	4 G 4	14,0 - 17,9	154,0	395,0	12	37092	7 G 1,5	14,7 - 18,7	101,0	375,0	16
37048	4 G 6	15,7 - 20,0	230,0	540,0	10	37079	7 G 2,5	17,1 - 21,8	168,0	520,0	14
37049	4 G 10	20,9 - 26,5	384,0	950,0	8	37093	12 G 1,5	17,6 - 22,4	175,0	460,0	16
37050	4 G 16	23,8 - 30,1	614,0	1260,0	6	37096	12 G 2,5	20,6 - 26,2	288,0	760,0	14
37051	4 G 25	28,9 - 36,6	960,0	1860,0	4	37097	18 G 2,5	24,4 - 30,9	432,0	850,0	14
37052	4 G 35	32,5 - 41,1	1344,0	2380,0	2	37094	19 G 1,5	20,7 - 26,3	274,0	810,0	16
37053	4 G 50	37,7 - 47,5	1920,0	3190,0	1	37098	19 G 2,5	25,5 - 31,0	456,0	1075,0	14
37054	4 G 70	42,7 - 54,0	2688,0	4260,0	2/0	37095	24 G 1,5	24,3 - 30,7	346,0	1015,0	16
37055	4 G 95	48,4 - 61,0	3648,0	5600,0	3/0	37099	24 G 2,5	28,8 - 36,4	576,0	1390,0	14

Dimensions and specifications may be changed without prior notice. (RF01)



Suitable accessories can be found in Chapter X.

- Cable tie - T-W5

F