

FEATURES

- Male-to-male HDMI high-speed cable
- Active boosted cable (input/output must be correctly installed)
- Oxygen-free copper for quality transmission
- Double-shielded against interference
- HDMI Ethernet and audio return channel in one
- 3D over HDMI
- 4k maximum resolution
- USB connection for extra power
- Outer diameter of 7.3mm
- Internal wire size of 0.254 mm, 0.32 mm

RS PRO 4K - HDMI to HDMI Cable, Male to Male- 20m

RS Stock No.: 182-8810



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

Made from oxygen-free copper for improved transmission, this male-to-male HDMI cable from the RS PRO range provides a quality connection for audio-visual devices. As an active boosted cable, it uses a silicon chip to boost the signal along its 20-metre length without any quality loss.

General Specifications

Cable Type	HDMI to HDMI
Connector A	Male HDMI
Connector A Gender	Male
Connector A Type	HDMI
Connector B	Male HDMI
Connector B Gender	Male
Connector B Type	HDMI
Maximum Resolution	4K
Number of Shielding	2x
Outer Sheath Material	PVC
Sheath Colour	Black
Hood	Connector
Applications	Computer Monitors, Digital Broadcasting, Blu-Ray Players, Gaming Consoles

Mechanical Specifications

Length	20M
Size of Strands	0.254mm, 0.32mm
Wire Gauge	28AWG



Approvals


Compliance/Certifications	CE, REACH, RoHS Compliant
Standards Met	ANSI/ESD S20.20:2014, BS EN 61340-5-1:2007




HDMI Cables









AL+MY:5*(8+11)al/my/my
insulation:5pairs,FPE,OD:Ø1.15±0 02
conductor:5Cx[30AWG(1/0.254CUx1pair]
conductor:5Cx[28AWG(1/0.32CUx1pair]
conductor:4Cx30AWG(0.254CU)
insulation:7core,OD:Ø0.8±0.03,
HDPE(1 twisted)
AL/MY:AL/MY,0.025*30mm

DRAIN:16/6/0.12AL
jacket:Ø7.3±0.15mm
UL PVC,75P,black