



Benefits

- Excellent LED Illumination with glamorous classic shapes
- Emit light at an unobstructed and panoramic angle
- Create a well lit and cosy space
- Seamless dimming range from 100% to 20% for perfect atmosphere

Application



Model	Item Description	W	PF	lm	lm/W	CRI	BA	Beam Angle	Life (h)	Single Box (LxWxH)mm	Outer Box (LxWxH)mm	Packing Qty (PCS/CTN)
A60S1-D-5.5W-F-E27	SIGV1 A60 5.5W E27 FS 2800K DIM	5.5	>0.8	500	90	>80	240°	25000		59*59*105	378*315*235	60
LG7207d-E27	BULB A60 7W E27 MK 4000K DIM	7.0	>0.7	470	67	>80	240°	25000		59*59*105	378*315*235	60
A60S1-D-8.7W-E-E27	SIGV1 A60 8.7W E27 FS 3000K DIM	8.7	>0.7	1055	121	>80	240°	25000		59*59*105	378*315*235	60
LG7813d-E27	BULB A65 13W E27 MK 6500K DIM	13.0	>0.9	1055	81	>80	240°	25000		59*59*105	378*315*235	60

Application Conditions	
IP	IP20
Operating Temperature	-20~40°C
Application Temperature	25°C
Storage Environment	-25~50°C

Mechanical Properties	
Optical Material	PC
Housing Material	PBT
Finishing Colour	White

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC

Dimensional Drawing

