EZ9F56316

Miniature circuit breaker (MCB), Easy9, 3P, 16A, C curve, 6000A (IEC/EN 60898-1)





Main	
Range	Easy9
Device application	Distribution
Product or component type	Miniature circuit-breaker
Device short name	Easy9 MCB
Poles	3P
Number of protected poles	3
[In] rated current	16 A
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	С
Breaking capacity	10000 A Icn at 220 V AC 50/60 Hz conforming to IEC 60898-1 6000 A Icn at 400 V AC 50/60 Hz conforming to IEC 60898-1
Suitability for isolation	Yes conforming to IEC 60898-1

Comp	lementary	/
COMP	ioirioiriai y	

Network frequency	50 Hz
[Ue] rated operational voltage	220 V AC 50/60 Hz
	400 V AC 50/60 Hz
Magnetic tripping limit	510 x ln
[lcs] rated service breaking capacity	6 kA 100 % x Icn at 400 V AC 50/60 Hz conforming to IEC 60898-1
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to IEC 60898-1
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60898-1
Contact position indicator	Yes
Control type	Toggle
Local signalling	Without
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	6
Height	81 mm
Width	54 mm
Depth	66.5 mm
Colour	Grey (RAL 7035)
Mechanical durability	10000 cycles
Electrical durability	4000 cycles
Connections - terminals	Tunnel type terminal (top or bottom) 125 mm² rigid Tunnel type terminal (top or bottom) 116 mm² flexible
Tightening torque	2 N.m top or bottom

Environment

Standards	IEC 60898-1	
Product certifications	CE VDE	
IP degree of protection	IP20 conforming to IEC 60529	
Pollution degree	2	
Tropicalisation	2	
Relative humidity	95 % at -560 °C	
Ambient air temperature for operation	-560 °C	
Ambient air temperature for storage	-4085 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	5.3 cm
Package 1 Length	8.5 cm
Package 1 Weight	326 g
Unit Type of Package 2	BB2
Number of Units in Package 2	4
Package 2 Height	8.5 cm
Package 2 Width	9 cm
Package 2 Length	22 cm
Package 2 Weight	1326 g

Offer Sustainability

Green Premium product
REACh Declaration
Compliant EEU RoHS Declaration
Yes
Yes
China RoHS Declaration
₽¥Yes
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins