



ENGLISH

## RS Pro Datasheet

Black, flexible hose for fuel in automotive or engine application. High resistance to all above media and especially used in Car, Truck, Agricultural and Construction equipment vehicles for fuel injection systems. High temp hose with low permeation for Petrol at less than 15g/m<sup>2</sup>/24hrs. Normally installed using crimped ferrules or petrol hose clips. Suitable for petrol, diesel, ethanol, gasoline, oxidized sour gas, oil and biodiesel.

Intermittent Temperature: +150 °C

Please contact Codan for further information.

**Application:** Fuel / Diesel / Bio-diesel

**Standard Length:** 25 metres

**Working Temperature:** -30°C to 130°C

**Inside:** FKM/NBR

**Colour:** Black

**Reinforcement:** PET

**Outside:** CPE

**Colour:** Black

**Standards:** SAE J30 R9 and MGRES22RU49 Class 1A

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)
4,8	11,8	10	62	46	195
5,6	12,0	10	62	52	130
6,3	12,7	7	62	56	150
7,0	14,6	7	62	60	195
7,1	13,2	7	62	60	195
7,9	14,5	7	62	58	180
9,5	16,5	7	62	62	230
12,7	19,9	7	34	68	250
15,6	22,4	7	34	76	271