



MASTERColour CDM-TC Elite



MASTERC CDM-TC Elite 20W/830 G8.5 1CT/12

Compact, single-ended, very high-efficiency, long-life ceramic metal-halide discharge lamp producing crisp white sparkling light with high color rendering

Warnings and Safety

- · Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- \cdot The luminaire must be able to contain hot lamp parts if the lamp ruptures
- \cdot Use only with electronic control gear
- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	G8.5 [G8.5]
Operating Position	UNIVERSAL [Any or Universal (U)]
Flux measurement reference	Sphere
Life to 50% Failures (Nom)	20,000 hour(s)
Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux	1,750 lm
Color Designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	0.434
Chromaticity Coordinate Y (Nom)	0.398
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	87 lm/W

Color rendering index (CRI)	85				
Arc Length O (Nom)	4 mm				
Operating and Electrical					
Power Consumption	20.1 W				
Voltage (Nom)	95 V				
Voltage (Nom)	95 V				
Controls and Dimming					
Dimmable	No				
Mechanical and Housing					
Bulb Finish	Clear				
Bulb Material	UV-Block Quartz				


Datasheet, 2023, November 21 data subject to change

MASTERColour CDM-TC Elite

Bulb Shape	T14 [T 14 mm]				
Approval and Application					
Energy Efficiency Class	G				
Mercury (Hg) Content (Max)	3.5 mg				
Mercury (Hg) Content (Nom)	3.5 mg				
Energy Consumption kWh/1000 h	21 kWh				
EPREL Registration Number	473254				
Product Data					
Order product name	MASTERC CDM-TC Elite 20W/830 G8 5 1CT/12				


Full product name	MASTERC CDM-TC Elite 20W/830 G8.5 1CT/12
Full product code	872790087158600
Order code	928183405125
Material Nr. (12NC)	928183405125
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900871586
Numerator - Packs per outer box	12
EAN/UPC - Case	8727900871593

Dimensional drawing




Product	D (max)	D	0	L (min)	L (max)	L	C (max)
MASTERC CDM-TC Elite	15 mm	0.55 inch	4 mm	51 mm	53 mm	52 mm	85 mm
20W/830 G8.5 1CT/12							

Photometric data








Light Distribution Diagram - MASTERC CDM-TC Elite 20W/830 G8.5 1CT/12

Spectral Power Distribution Colour - MASTERC CDM-TC Elite 20W/830 G8.5 1CT/12

MASTERColour CDM-TC Elite

Lifetime





Life Expectancy Diagram - MASTERC CDM-TC Elite 20W/830 G8.5 1CT/12

Lumen Maintenance Diagram - MASTERC CDM-TC Elite 20W/830 G8.5 1CT/12



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.