A9A27108

Undervoltage release, Acti9 iMN, 24VAC/24VDC





Main

Range of product	Acti9
Product or component type	Undervoltage release
Device short name	iMN
Device application	Protection
[Uc] control circuit voltage	24 V AC 50/60 Hz 24 V DC
Control type	Toggle
9 mm pitches	2

Complementary

Protection type	Undervoltage
Range compatibility	Acti 9 Acti9 iDPN Vigi Acti 9 Acti9 iID Acti 9 Acti9 iSW-NA Acti 9 Acti9 iC60 double terminals miniature circuit breaker
Local signalling	Red indicator light on the front face
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Top and bottom: YES
Height	85 mm
Width	17.5 mm
Depth	73 mm
Net weight	69 g
Colour	White
Connections - terminals	Clamp terminal (bottom) - 1 cable(s) 16 mm² - rigid without cable end Clamp terminal (bottom) - 1 cable(s) 0.54 mm² - flexible without cable end Clamp terminal (bottom) - 2 cable(s) 12.5 mm² - rigid without cable end Clamp terminal (bottom) - 2 cable(s) 12.5 mm² - rigid with cable end
Wire stripping length	10 mm for bottom connection
Tightening torque	1 N.m bottom
Compatibility code	IMN

Environment

Standards	EN/IEC 60947-5-1	- 3
Ambient air temperature for operation	-3570 °C	- 5
Ambient air temperature for storage	-4085 °C	- :

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3 cm	
Package 1 Width	7.7 cm	
Package 1 Length	9.4 cm	
Package 1 Weight	78 g	

Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	8.7 cm
Package 2 Width	10 cm
Package 2 Length	26.7 cm
Package 2 Weight	684 g
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	6.658 kg

Offer Sustainability

kets following specific
()