



Main

| | |
|---------------------------|----------------------|
| Range | Vivace |
| Device short name | KB30 |
| Product or component type | Fuse connection unit |
| Device application | Power supply |
| Device presentation | Complete mechanism |
| Main colour tint | White |
| Colour tint | Wall: white |

Complementary

| | |
|------------------------------|--|
| Colour tint | White |
| Material | Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base |
| Projecting depth | 8 mm |
| Device mounting | Surface Flush |
| Mounting support | Wall mounted |
| Fixing mode | By screw M3.5 |
| Fixing center | 60.3 mm |
| Embedding depth | 35 mm |
| Rated current | 13 A at 250 V AC, resistive |
| Network frequency | 50 Hz |
| Contacts material | Brass and phosphor bronze |
| Connections - terminals | Pillar terminal |
| Terminal identifier | L in L out N in N out Earth |
| Tightening torque | 0.4 N.m |
| Clamping connection capacity | 2 x 4 mm ² power circuit 3 x 2.5 mm ² incoming 1 x 1.5 mm ² outgoing 1 x 2.5 mm ² input |
| Width | 87 mm |
| Height | 87 mm |
| Depth | 35 mm |

Environment

| | |
|---------------------------------------|------------|
| Standards | BS 1363-4 |
| Ambient air temperature for operation | -5...40 °C |
| Ambient air temperature for storage | 0...60 °C |
| Relative humidity | 0...95 % |
| Operating altitude | 0...2000 m |
| Environmental characteristic | Indoor use |
| IP degree of protection | IP20 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.6 cm |
| Package 1 Width | 3.5 cm |
| Package 1 Length | 14.6 cm |
| Package 1 Weight | 116.9 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 9.5 cm |
| Package 2 Width | 15 cm |
| Package 2 Length | 19 cm |
| Package 2 Weight | 1.239 kg |
| Unit Type of Package 3 | CAR |
| Number of Units in Package 3 | 100 |
| Package 3 Height | 21 cm |
| Package 3 Width | 31.5 cm |
| Package 3 Length | 50 cm |
| Package 3 Weight | 11940 g |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|