

Eaton 170M2669

Catalog Number: 170M2669

Fuse-link, high speed, 315 A, AC 690 V, DIN 00, aR, DIN, IEC, single indicator, live gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M2669
	UPC
	051712799195
EAN	Product Length/Depth
5027590442466	98 mm
Product Height	Product Width
51 mm	28 mm
Product Weight	Compliances
211.833 g	RoHS Compliant
	CE Marked
Certifications	
IEC Rated	
UL Recognized	

Product specifications

Fuse indicator

Other

Interrupt rating

200 kAIC

Construction size

Other

Clearing (I2T)

68500 at 660 V

Rated voltage AC

690 V

Color

None

Insulated metal gripping lugs (IMGL)

No

Connection

Blade end x blade end

Current type

AC

Amperage Rating

315 A

Utilization category

aR (accompanied semiconductor protection)

Watt losses

55 W

Fuse type

DIN 43653

TN/80 Type T Indicator for Micro

Type

Fuse

Fuse shape

Square body, slotted offset bolted tags

Breaking capacity

200 kA

Fuse size

00

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

Compliance information

CE 170M Size 00, rated 690 Vac, up to 400A

UKCA 170M Size 00, rated 690 Vac, up to 400A

Class

Class aR

Pre arc (I2T)

10000

Voltage rating

690 V (IEC), 700 V (UL)

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Voltage type

AC



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)