



### Main

|                           |                         |
|---------------------------|-------------------------|
| Range                     | Vivace                  |
| Product or component type | Switch                  |
| Device short name         | KB31                    |
| Device application        | Control                 |
| Switch function           | Double 1-way with earth |

### Complementary

|                                |   |
|--------------------------------|---|
| Device presentation            | Complete mechanism  |
| Actuator                       | Rocker  |
| Pilot light                    | Neon indicator lamp   |
| Number of gangs                | 1 gang  |
| Colour tint                    | Aluminium silver  |
| Material                       | Polycarbonate: grid plate<br>Polycarbonate: surround<br>Nylon: base |
| Projecting depth               | 8 mm  |
| Device mounting                | Flush   |
| Mounting support               | Wall mounted  |
| Fixing mode                    | By screw M3.5   |
| Fixing center                  | 60.3 mm   |
| Embedding depth                | 35 mm   |
| Rated current                  | 20 A at 250 V AC, inductive<br>20 A at 250 V AC, resistive          |
| [Ue] rated operational voltage | 250 V AC  |
| Network frequency              | 50 Hz   |
| Contacts material              | Brass and phosphor bronze   |
| Connections - terminals        | Pillar terminal   |
| Terminal identifier            | L2<br>N2<br>L1<br>N1  |
| Tightening torque              | 0.4 N.m   |
| Clamping connection capacity   | <= 2.5 mm <sup>2</sup>  |
| Width                          | 86 mm   |
| Height                         | 86 mm   |

### Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | SS 227<br>IEC 60669-1<br>MS IEC 60669-1 |
| Ambient air temperature for operation | -5...40 °C                              |
| Relative humidity                     | 0...95 %                                |
| Environmental characteristic          | Indoor use                              |

## Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant with Exemptions                     |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#">Yes</a>                           |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |
| Circularity Profile        | No need of specific recycling operations      |