

Datasheet

Stock No:1706969

RS Pro

ANTI-VIBRATION MMCX STRAIGHT SURFACE MOUNT JACK RECEPTACLE

RECOMMENDED LAND PATTERN

APPROVED by _____ DATE: _____

1.0 ELECTRICAL

- 1.1 FREQUENCY RANGE: DC-12 GHz
- 1.2 NOMINAL IMPEDANCE: 50 OHMS
- 1.3 VOLTAGE RATING: 250 VOLTS MAX.
- 1.4 VSWR: 1.22 MAX. @6 GHz

2.0 MATERIALS

- 2.1 BODIES: BRASS PER IEC C2604
- 2.2 CENTER CONTACT: BERYLLIUM COPPER PER ASTM B196 UNS C1730
- 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D7110

3.0 FINISHES AND OTHERS

- 3.1 SEE BELOW TABLE FOR DETAILS.

4.0 MECHANICAL

- 4.1 INTERFACES IN ACCORDANCE WITH: BS EN 122340

5.0 ENVIRONMENTAL

- 5.1 OPERATING TEMPERATURE RANGE: -55 C TO +155 C

NO	DESCRIPTION	MATERIAL	QTY	FINISH
4	TAPE	PT	1	NONE
3	CENTER CONTACT	BERYLLIUM COPPER	1	GOLD 30 μ" MIN.
2	INSULATION	TEFLON	1	NONE
1	BODY	BRASS	1	GOLD 3 μ" MIN.
NO	DESCRIPTION	MATERIAL	QTY	FINISH

DESCRIPTION	TOLERANCE	品名	DATE	REV.
ANTI - VIBRATION MMCX STRAIGHT SURFACE MOUNT JACK RECEPTACLE	(S02)	40370208300013	12.05.17	A-0
Jackie	±0.2	TITLE (ROHS COMPLIANT)	日	次
ARC	±0.1	UNIT (mm(m))		
Jenny	±0.05	DWG.NO. 37-0095-Z		
ANGLE ±5°	SCALE			
8:1	例			