



ENGLISH

Datasheet

RS PRO RRB 0315 tool for crimping Super Seal type open barrel connectors 0.35 - 1.5 mm² with silicon seals

Stock No: 6810-0739



Features & Benefits:

- Unique "snap on" locator design for full visibility of connector and wire insertion
- Parallel action for precision and consistent crimp results
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miss-crimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Tool-less die closure adjustment for maintenance and calibration
- Small size makes it easy to use in confined areas
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability

Crimp Die Set

4362 22-20-4 20 16 0.35-0.5 0.75-0.5 0.75-4362 mm²

Crimp Profile



TECHNICAL DATA

Length: 190 mm/7.48" Width: 21 mm/0.83" Height: 74 mm/2.91"

Weight: 317 gr/0.7 lb

Wire size: 0.35-1.5 mm² / AWG 22-AWG 16

Crimp dimensions mm/mm²:

0,35 - 0,5/0,75 - 1,5

Crimp dimensions inch/AWG:

AWG 22 - AWG 20/AWG 20 - AWG 16

Connector: Connectors with seal, 1.5 system type.

Description: For non insulated open barrel super seal

connectors.

Life span, cycles: 50,000



