



Main

Range	Ulti
Device application	Control
Product or component type	Switch module
Load type	Incandescent lamp
Switch application	Switch

Complementary

Bulb type	LED blue
Rated current	20 A at 220...250 V AC 50/60 Hz
Number of cables	4 cable(s) 6 mm ²
Opening distance	> 3 mm
Device mounting	Flush Surface
Fixing mode	By screws
Distance between centers	60.3 mm
Operating mode	Manual
Number of gangs	1 gang
Switch function	2-pole
Width	87 mm
Height	87 mm
Depth	24 mm

Environment

Ambient air temperature for operation	0...35 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	0...95 %
Standards	BS EN 60669-1 IEC 60669-1
Environmental characteristic	No UV resistant
IP degree of protection	IP2X
Operating altitude	<= 2000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.1 cm
Package 1 Width	8.4 cm
Package 1 Length	8.6 cm
Package 1 Weight	194.35 g
Unit Type of Package 2	CAR

Number of Units in Package 2	30
Package 2 Height	18 cm
Package 2 Width	31.2 cm
Package 2 Length	56.3 cm
Package 2 Weight	5830.5 g
Unit Type of Package 3	PAL
Number of Units in Package 3	600
Package 3 Height	100 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	116610 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations