


FEATURES

- UL approved Nylon 66, 94V-2
- Color: Black, other special colors are available upon request.
- Press the tie into a pre-drilled hole and bind the cord by securing the tie.

RS PRO Push Mount Tie

RS Stock No.: 2243188



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

ATTRIBUTE 1

- Material: UL approved Nylon 66 , 94V-2.
- Color: Black
- Press the tie into a pre-drilled hole and bind the cord by securing the tie.

General Specifications

Series	Push Mount Tie
Type	Non-Releasable
Colour	Black
Material	Nylon 66
Finish	
Application	
Resistant To	
UV Resistant	No
Minimum Operating Temperature	-40°C
Maximum Operating Temperature	85°C
Fire Behaviour	Self-Extinguishing
Quantity	100

Mechanical Specifications

Length	170mm(6 11/16")
Width	4.8mm
Max. Bundle Dia.	40mm
Mounting Hole	6.0mm
Chassis Thickness	3.0mm
Tensile Strength	50lbs/22Kgs
Thickness	1.3±0.25mm

Protection Category

IP Rating

Classification

eCl@ss (10.0.1)

UNSPSC (6.01)

Approvals

Declarations

Standards Met

UL, RoHS, SVHC, HF, ABS

Similar Products

Stock No.	Brand	Product Name	Colour	Material	Tensile strength
178-9501	RS	Push Mount Tie	Natural	Nylon66	50lbs/22kgs

