





LIGHT MODULE ELLIPTICAL LIGHT TOWER



P.N. 190-2817, 190-2818, 190-2819, 190-2820, 190-2821, 190-2822

Modulo luminoso a led.

Led luminous module.
Module lumineux à LED
LED-Lichtmodul
Módulo de luz LED

CUPOLA DOME DOME HAUBE CÚPULA	PC							
GUARNIZIONE GASKET JOINT DICHTUNG JUNTA	O-Ring Silicone							
GRUPPO OTTICO LUMINOUS SOURCE SOURCE LUMINEUSE LICHTQUELLE FUENTE DE LUZ	N°6 LED							
COLORI DISPONIBILI AVAILABLE COLOURS COULEURS DISPONIBLES VERFÜGBARE FARBEN COLORES DISPONIBLES								
TENSIONE DI ALIMENTAZIONE VOLTAGE TENSION SPANNUNG TENSIÓN	24V ac/dc, 240V ac							
SERVIZIO OPERATION FONCTIONNEMENT BETRIEBSART FUNCIONAMIENTO	∞							
CORRENTE NOMINALE CURRENT CONSUMPTION CONSOMMATION DE COURANT STROMAUFNAHME CONSUMO DE CORRIENTE			12 Vdc	12 Vac	24 Vdc	24 Vac	120 Vac	240 Vac
RESA LUMINOSA LIGHT OUTPUT RENDEMENT LUMINEUX LICHT LEISTUNG SALIDA DE LUZ								
MODALITA' LUCE LIGHT EFFECT EFFET LUMINEUX LICHTEFFEKT EFECTO LUMINOSO	Fissa / Lampeggiante <i>Steady/Flashing</i> <i>Fixe/Clignotant</i> <i>Dauerlicht/ Blinklicht</i> <i>Luz fija/ intermitente</i>							
FLASH/MIN FLASHES PER MINUTE ECLATS PAR MINUTE FLASH / MIN FLASHES POR MINUTO	1F X 75, 2F X 90, 3F X 72, 5F X 70							

Dati diffusi a solo scopo informativo. Sirena S.p.A. puo' modificare i dati in qualsiasi momento senza preavviso.
 These data are disclosed only for information purposes. Sirena S.p.A. reserves the right to modify them at any time without prior notice.
 Les données ne sont divulguées qu'à titre d'information. Sirena S.p.A. se réserve la faculté de les modifier à tout moment sans préavis



SCHEDA TECNICA
Technical data sheet
Fiche technique

05/09/19

GRADO IP IP RATING DEGRE IP SCHUTZART GRADO IP	IP66
TEMPERATURA DI FUNZIONAMENTO OPERATING TEMPERATURE TEMPERATURE DE SERVICE BETRIEBSTEMPERATUR TEMPERATURA DE FUNCIONAMIENTO	-30°C+50°C
VIBRAZIONI VIBRATIONS VIBRATIONS VIBRATIONEN VIBRACIONES	INDUSTRIAL CEI 60068-2-6 SINE
CERTIFICAZIONI, OMOLOGAZIONI CERTIFICATIONS, APPROVALS CERTIFICATIONS, HOMOLOGATIONS PRODUKTZERTIFIKATE, ZULASSUNGEN CERTIFICADOS, HOMOLOGACIONES	CE
FISSAGGIO MOUNTING FIXATION FIXIERUNG FIJACIÓN	A incastro Stackable A encastrement Stapelbar Apilable
DISEGNO TECHNICAL DRAWING DESSIN TECHNISCHE ZEICHNUNG DIBUJO TECNICO	<p>The technical drawing consists of two views. The left view is a side profile of a rectangular component with a height of 43 and a width of 35. The right view is a top-down view of a circular component with a diameter of 70 and a central rectangular feature with a height of 50.</p>

Dati diffusi a solo scopo informativo. Sirena S.p.A. puo' modificare i dati in qualsiasi momento senza preavviso.
These data are disclosed only for information purposes. Sirena S.p.A. reserves the right to modify them at any time without prior notice.
Les données ne sont divulguées qu'à titre d'information. Sirena S.p.A. se réserve la faculté de les modifier à tout moment sans préavis