

Datasheet

Stock No:1706990

# RS Pro N STRAIGHT PLUG-PLUG ADAPTER

NO	DESCRIPTION	DATE
A	61-22/R61-022-00-00B110JQ →40610906100003	02.05.18

  

APPROVED \_\_\_\_\_ by \_\_\_\_\_ DATE: \_\_\_\_\_

  

**1.0 ELECTRICAL**

1.1 FREQUENCY RANGE: DC-11 GHz

1.2 NOMINAL IMPEDANCE: 50 OHM

1.3 VOLTAGE RATING: 1000 VOLTS MAX.

1.4 VSWR: 1.1 MAX @6 GHz

1.3 MAX @11 GHz

**2.0 MATERIALS**

2.1 BODIES: BRASS PER JS-C3604

2.2 CENTER CONTACT: BRASS PER JS-C3604

2.3 INSULATION: TEFLON PER ASTM D467 AND ASTM D4710

**3.0 FINISHES AND OTHERS**

3.1 SEE BELOW TABLE FOR DETAILS.

**4.0 MECHANICAL**

4.1 INTERFACE IN ACCORDANCE WITH: MIL-STD-348A

**5.0 ENVIRONMENTAL**

5.1 OPERATING TEMPERATURE RANGE: -65° C TO +165° C

NO.	DESCRIPTION	MATERIAL	QTY	FINISH
7	SHELL	BRASS	2	WHITE BRONZE 80 μ MIN
6	CHASSIS	BRASS	1	WHITE BRONZE 80 μ MIN.
5	GASKET	SILICONE	2	RED
4	WASHER	BRASS	2	NONE
3	BODY	BRASS	1	WHITE BRONZE 80 μ MIN.
2	CENTER CONTACT	BRASS	1	GOLD 3 μ MIN.
1	INSULATION	TEFLON	1	NONE

  

DESCRIPTION	N STRAIGHT PLUG-PLUG ADAPTER				
DRAWN	TOLERANCE	品名	40610906100003/A	DATE	REV.
Jackie	X ±0.2	TITLE	ROHS COMPLIANT (5000)	09.2+13	A-1
CHECK	XX ±0.1	UNIT	mm(In)		
A7c	XXX ±0.05	DWG. NO.	61-0007-Z		
APPROVAL	ANGLE ±5	SCALE			
Jenny	4:1				