



Safe-D 25mm Conduit Clip - Galvanised



Provides a 3mm stand off from the surface



Simply wrap around the conduit, perfect for tight spaces



Secure conduit with locking tab



Centralised base fixing, gives a neat appearance to installation

Safe-D Conduit Clips combine fire performance, quickest fix, and a modern look, to secure cables in 25mm outer diameter galvanised conduit installations... (or exposed 25mm o/d cables and pipes.)


Compared to traditional saddles, where lids must be secured to bases, there is no separate lid - the conduit (and cables) is held by the wrap-design, which has an end tab that simply fits through the opposing notch to enable a secure lock.

The tight wrap, that eliminates need for wide-bases, is ideal also for installations in tight spaces.

1 piece for only 1 fixing!

- Fully safety tested, for compliance with BS7671 and BS5839 part 1
- Produced from steel with >1200°C melting point
- Non-corrosive finish
- Unique single piece fixing, only 1x screw required
- Fixing hole is ideal for use with D-Fixings
- Also available in white or black finish

In fire conditions, Conduit Clips can withstand 970°C for at least 2 hours, ensuring that cable installations will not collapse to cause potentially fatal entanglements.



Code	Description
1823861	(L) 100mm x (W) 20mm x (H) 28mm (folded - max height) 5.7mm diameter pre-drilled hole in base