ESD Safe Soldering Station





Features

- LCD display
- MCU controlled temperature calibration
- 3 Preset and 2 variable button adjustment
- On / Off switch on side unit
- Pluggable four-core heating element
- Includes main unit, handle set, iron stand, AC power cord, sponge and manual

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk





Technical Specifications

Voltage	: AC (220V ~ 240V) 50Hz
Power	: 80W
Heater Voltage	: 26V AC
Temperature Range	: 150°C to 480°C (302°F to 896°F)
Temperature Offset Range	: ±50°C / ±90°F
Temperature Stability	: ±2°C (still air, no load)
Temperature Accuracy	: ±10°C
Heater	: High quality pluggable four-core heating element
Tip to Ground Impedance	: < 2Ω
Tip to Ground Voltage	: < 2mV
Dimension (L × W × H)	: 146mm × 120mm × 91mm
Weight	: 1.8kg

Part Number Table

Description	Part Number
Soldering Station, ESD Safe, 80W, 220V AC, 480°C Max. Temp., UK Plug	21-21310 UK
Soldering Station, ESD Safe, 80W, 220V AC, 480°C Max. Temp., EU Plug	21-21310 EU

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

