High-pressure Wash and Tire-Fill Pump Package

High-power cleaning solutions

Perfect for cleaning:

With the application of:

- Cars and trucks
- Engines
- · Construction equipment
- Aircraft
- · Farm equipment · Plant structures
- · Railroad equipment
- · Fleet vehicles

- Degreasers
- Detergents
- · Cleaning solutions
- Water
- · Metal brighteners
- Aluminum brighteners



Wash Pumps

	9:1 Ratio
Lower Pump Material	Stainless Steel
Air Motor Diameter	4 1/4"
Air Inlet Pressure Range psi (bar)	0-150 (0-10.3)
Fluid Pressure Range psi (bar)	0-1500 (0-103)
Stroke Length	4"
Max. Recommended Cycles /	60
Flow Rate gpm (lpm)	2.9 (10.8)
Cycles Per Gallon (Liter)	21 (5.5)
Air Inlet Size	½″ (F)
Fluid Outlet Size	³ / ₄ " (F)
Fluid Inlet Size	Barbed
Noise Level @ 60 psi – 40 cpm	89.2 db(A)

Packings type / material Model upper lower			
BASIC PUMPS			
STUB 4-1/4" DIAMETER AIR MOTOR / 4" STROKE			
AF0409C81BBW2	Buna N	Buna N	

Model	Description
SPRAY WASH PUMF	P PACKAGE - 55 GALLON CONTAINER
WP0409C81BBW2000	4-1/4" (107.9 mm) High-pressure wall-mounted spray package includes AF0409C81BBW2 pump, 61113 wall bracket, 61139-1 55-gal suction tube assembly, 622427-40 material hose (40' / 12.2 m), 641523 control handle, 61133 spray wand, TP6250-18 spray tip and L26241-010 Air Line
	lubricator

Dollies, Hand Trucks

5-GAL DRUM		
Platform-type dolly has four swivel casters and three drum clamps; for use with steel or fiber drums		
Band-type dolly has four rubber-wheeled casters and screw clamp; for use with steel or fiber drums		
HAND TRUCKS		
16-GAL DRUM		
Two-wheel truck has clamp rod and two base supports to hold drum; wheels are rubber		
Three-wheel truck includes hinged handle, swivel-type front wheel, and two 6" (152 mm) rubber rear wheels		

