



Revision Number: 008.0

Issue date: 03/22/2017

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product name:</b>	LOCTITE SI 596 RD AE known as LOCTITE® SUPERFLEX® RED HIGH T	<b>IDH number:</b>	743520
<b>Product type:</b>	Silicone	<b>Item number:</b>	40465
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	<b>Contact information:</b>	Telephone: (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**DANGER:** CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.  
CAUSES SKIN IRRITATION.  
MAY CAUSE AN ALLERGIC SKIN REACTION.  
CAUSES SERIOUS EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
GASES UNDER PRESSURE	Compr. Gas
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1

**PICTOGRAM(S)**



**Precautionary Statements**

**Prevention:** Avoid breathing mist or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

**Response:** IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing.

**Storage:** Protect from sunlight. Store in a well-ventilated place.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Hazardous Component(s)	CAS Number	Percentage*
Distillates (petroleum), hydrotreated middle	64742-46-7	5 - 10
Silicon dioxide	7631-86-9	5 - 10
Norflurane	811-97-2	5 - 10
Siloxanes and Silicones, di-Me	63148-62-9	1 - 5
Diiron trioxide	1309-37-1	1 - 5
Methylsilanetriyl triacetate	4253-34-3	1 - 5
Triacetoxyethylsilane	17689-77-9	1 - 5
Acetic acid	64-19-7	0.1 - 1
Gamma-glycidoxypropyl trimethoxysilane	2530-83-8	0.1 - 1
Barium sulfate	7727-43-7	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
<b>Skin contact:</b>	Wipe off paste with paper towel or cloth. Wash with soap and water. If symptoms develop and persist, get medical attention.
<b>Eye contact:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Ingestion:</b>	Do not induce vomiting. If a person feels unwell or symptoms of skin irritation appear, consult a physician.
<b>Symptoms:</b>	See Section 11.

#### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	None
<b>Unusual fire or explosion hazards:</b>	None
<b>Hazardous combustion products:</b>	Oxides of carbon. Oxides of silicon. Formaldehyde.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Scrape up as much material as possible. Store in a partly filled, closed container until disposal.

## 7. HANDLING AND STORAGE

**Handling:** Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not wear contact lenses.

**Storage:** For safe storage, store between 8 °C (46.4 °F) and 28 °C (82.4 °F) Store in a dry area below 90° F.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated middle	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist. 100 ppm (400 mg/m3) PEL	None	None
Silicon dioxide	6 mg/m3 TWA	20 MPPCF TWA 0.8 mg/m3 TWA	None	3 mg/m3 TWA Respirable fraction.
Norflurane	None	None	1,000 ppm (4,240 mg/m3) TWA	None
Siloxanes and Silicones, di-Me	None	None	None	None
Diiron trioxide	5 mg/m3 TWA Respirable fraction.	10 mg/m3 PEL Fume. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Methylsilanetriyl triacetate	None	None	None	None
Triacetoxylethylsilane	None	None	None	None
Acetic acid	15 ppm STEL 10 ppm TWA	10 ppm (25 mg/m3) PEL	None	None
Gamma-glycidoxypropyl trimethoxysilane	None	None	None	None
Barium sulfate	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust.	None	None

**Engineering controls:** Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:** Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Aerosol
<b>Color:</b>	Red
<b>Odor:</b>	Acetic acid
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not available.
<b>Vapor pressure:</b>	Not available.
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	1.01 at 20 °C (68°F)
<b>Vapor density:</b>	Heavier than air
<b>Flash point:</b>	> 93 °C (> 199.4 °F)
<b>Flammable/Explosive limits - lower:</b>	Not applicable
<b>Flammable/Explosive limits - upper:</b>	Not applicable
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not applicable
<b>Solubility in water:</b>	Polymerises in presence of water.
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	3.08 %; 32.00 g/l Estimated
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Oxides of silicon. Formaldehyde.
<b>Incompatible materials:</b>	Acids and bases. Oxidizing agents.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Excessive heat.

## 11. TOXICOLOGICAL INFORMATION

<b>Relevant routes of exposure:</b>	Skin, Inhalation, Eyes
-------------------------------------	------------------------

### Potential Health Effects/Symptoms

**Inhalation:** Inhalation of vapors from uncured sealant may cause respiratory tract irritation. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit. Inhalation of vapors or mists of the product may be irritating to the respiratory system.

**Skin contact:** Causes skin irritation. May cause allergic skin reaction.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** Not expected under normal conditions of use. May be harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Distillates (petroleum), hydrotreated middle	None	Irritant
Silicon dioxide	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg	Nuisance dust
Norflurane	None	Cardiac, Central nervous system, Irritant, Respiratory, Skin
Siloxanes and Silicones, di-Me	None	Irritant
Diiron trioxide	None	Allergen, Cardiac, Central nervous system, Irritant, Kidney, Liver, Lung
Methylsilanetriyl triacetate	None	Irritant, Allergen
Triacetoxylethylsilane	None	No Target Organs
Acetic acid	Oral LD50 (Rabbit) = 1,200 mg/kg Oral LD50 (Mouse) = 4,960 mg/kg Oral LD50 (Rat) = 3.53 g/kg Oral LD50 (Rat) = 3.31 g/kg Dermal LD50 (Rabbit) = 1,060 mg/kg Inhalation LC50 (Rat, 4 h) = 11.4 mg/l	Allergen, Corrosive, Eyes, Gastrointestinal, Immune system, Irritant, Kidney
Gamma-glycidoxypropyl trimethoxysilane	None	Allergen, Irritant
Barium sulfate	None	Lung

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated middle	No	No	No
Silicon dioxide	No	No	No
Norflurane	No	No	No
Siloxanes and Silicones, di-Me	No	No	No
Diiron trioxide	No	No	No
Methylsilanetriyl triacetate	No	No	No
Triacetoxylethylsilane	No	No	No
Acetic acid	No	No	No
Gamma-glycidoxypropyl trimethoxysilane	No	No	No
Barium sulfate	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal. Do not puncture or incinerate pressurized containers.

**Hazardous waste number:** D005. Barium. D007. Chromium.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Aerosols  
**Hazard class or division:** 2.2  
**Identification number:** UN 1950  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Aerosols, non-flammable  
**Hazard class or division:** 2.2  
**Identification number:** UN 1950  
**Packing group:** None

### Water Transportation (IMO/MDG)

**Proper shipping name:** AEROSOLS  
**Hazard class or division:** 2.2  
**Identification number:** UN 1950  
**Packing group:** None

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.  
**CERCLA/SARA Section 311/312:** Immediate Health, Sudden Release  
**CERCLA/SARA Section 313:** None above reporting de minimis.

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

**Prepared by:** Regulatory Affairs

**Issue date:** 03/22/2017

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.