



TLP HUANHU Hydraulic Equipment

Hydraulic Pipe Bender, Separable Type



HHW-2F, HHW-3F, HHW-4F

Electric Hydraulic Pipe Bender



HHW-2D, HHW-3D, HHW-4D

Model	Capacity (T)	Max.stroke (mm)	Bending range (mm)	Bending formers (in)	Pipe wall thickness (mm)	weight (kg)	Volume (mm)
HHW-2F	13	250	φ21.3-φ60	1/2" 3/4" 1" 1 1/4" 1 1/2" 2"	2.75-4.5	50	730X320X200
HHW-3F	20	320	φ21.3-φ88.5	1/2" 3/4" 1" 1 1/4" 1 1/2" 2" 2 1/2" 3"	2.75-5	112	940X400X210
HHW-4F	23	370	φ21.3-φ108	1/2" 3/4" 1" 1 1/4" 1 1/2" 2" 2 1/2" 3" 4"	2.75-6	157	1180X460X230

Model	Capacity (T)	Max.stroke (mm)	Bending range (mm)	Bending formers (in)	Wall thickness of pipe (mm)	G.W. (Kg)	Volume (mm)
HHW-2D	13	250	φ21.5-φ60	1/2" 3/4" 1" 1 1/4" 1 1/2" 2"	2.75-4.5	74	960X350X270
HHW-3D	20	290	φ21.5-φ88.5	1/2" 3/4" 1" 1 1/4" 1 1/2" 2" 2 1/2" 3"	2.75-5	126	1180X460X270
HHW-4D	23	370	φ21.5-φ108	1/2" 3/4" 1" 1 1/4" 1 1/2" 2" 2 1/2" 3" 4"	2.75-6	174	1180X460X320

Multi-functional Pipe Bender



HHW-40A

Model	HHW-40A	
Max pipe size(mm)	● φ40 ■ 40X40X1 L 30X30	
Bending formers(mm/in)	φ40(1 1/2") φ32(1 1/4") φ25(1") φ20(3/4") φ16(5/8")	
Bending angle	α ≤ 180°	
Rotate speed of main shaft (r/min)	1400	
(Motor)	Power(KW)	3
	Voltage(V)	220/380
	Frequency(Hz)	50
G.W. (Kg)	335	
Volume (mm)	1010X610X1150	

Electric Ring Bender



HHW-76B

Name	HHW-76B
Round formers	16,19,22,25,32,38,51,63,76
Square formers	16,19,22,25,30,38,40,50
Pipe wall thickness	0.5-2
Motor	220/380
G.W.	260
Volume	730X630X1030