

PIG™ Pipe Wrap Repair Kit for Lines & Joints Not Under Pressure

PTY120 Non-Pressurized, For 2.5" - 4" dia.

Fast, easy way to permanently fix broken, corroded or leaking pipes to beyond their original strength.

- Each kit contains materials for restoring one unpressurized pipe or joint
- Works on most pipes, including PVC, copper, galvanized steel, rubber, lead and iron
- Materials adhere to wet or dry surfaces to allow repairs without draining pipes
- Butyl patch or PIG® Repair Putty applies underneath outer wrap to strengthen seal
- Polyurethane-impregnated fiberglass wrap exceeds original bursting pressure rating of pipes
- Nitrile gloves protect hands during repair
- Cures in approximately 30 minutes at 75°F
- Final repair is not affected by salt water
- NSF Certified for safe use on potable water lines



Specifications

| | |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Cure Time | 30 Minutes at 75°F (24°C) |
| Pipe Size | 2.5" - 4" dia. |
| Pipe Pressure | Non-Pressurized |
| Temperature Limit | 300°F (149°C) Continuous/500°F (260°C) Intermittent |
| Sold as | 3 per box |
| Weight | 3.208 lbs. |
| # per Pallet | 432 |
| Composition | Putty - Epoxy Patch - Butyl Gloves - Nitrile Wrap - Polyurethane/Fiberglass |
| Includes | 3 - 2.5"L Putty Sticks 1 - 4"L x 4"W Butyl Patch 1 - Pair Nitrile Gloves 1 - 15'L x 4"W Polyurethane-impregnated Fiberglass Wrap |
| Shelf Life | 2 years |
| UNSPSC | 31201519 |

Metric Equivalent

| | |
|---------------|--------|
| Weight | 1.5 kg |
|---------------|--------|

Technical Information

Certifications, Approvals and Ratings

NSF Certified

CountryNoShip

This product is subject to export restrictions and cannot be shipped to: Canada, European Union, Japan.

Certifications, Approvals and Ratings

NSF Certified

CountryNoShip

This product is subject to export restrictions and cannot be shipped to: Canada, European Union, Japan.

Technical Documents

Instructions for Using PIG® Pipe Wrap Repair Kit on Pipes Not Under Pressure

PIG® Multi-Purpose Repair Putty

PIG® Wrap for Pipes



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com